

## LECTUS duo 3000 classic line



- ▶ 13.56 MHz MIFARE readers compatible with Bosch access controller, as well as the Bosch software (BIS/ACE, AMS and APE)
- ▶ RS485 and Wiegand interface on all readers for highest flexibility
- ▶ Support of Bosch coded MIFARE Classic credential
- ▶ IP65 and IK08/IK10 ratings allow indoor and outdoor installations
- ▶ OSDP V2 Secure Channel support

### System overview

The LECTUS duo classic family comes in an attractive mullion design for wall and mullion mounting. The keypad version can be used to enter a PIN Code; or activate a custom feature like a long term open state of an entrance.

The LECTUS duo readers are fully compatible with the Bosch access management portfolio, including the management software systems (BIS/ACE, AMS and APE), the access modular controllers (AMC2) and the MIFARE and card technologies.

The support of 13.56MHz credential formats offers a migration path for proximity installations.

The reader is easily configurable via DIP switch settings to enable and disable MIFARE Classic reading and CSN or Bosch code reading only.

The user can configure the reader to read either Bosch coded MIFARE Classic credentials or the MIFARE Classic ISO14443A CSN.

During the operation, the user receives feedback from three LED indicators and a beeper. The logo on the reader is illuminated in the dark.

The reader is IP65 rated and appropriate for indoor and outdoor use.

### Certifications and approvals

Region	Regulatory compliance/quality marks
Europe	CE

Region	Regulatory compliance/quality marks
Global	RoHS
USA	FCC

### Installation/configuration notes

The LECTUS duo readers can be connected via the Wiegand interface, or through the RS485 interface, for cost effective serial connection.

The easy reader configuration options via DIP switches allow easy migration and fast customization in order to save time and costs.

The settings can easily be changed from reading ISO 14443A CSN only to Bosch code, by using a MIFARE Classic card.

The automation mode allows detection of Bosch code or CSN when present.

The LECTUS duo classic line is complemented by the LECTUS duo DESFire line.

The state of the art security is achieved at its highest level through encrypted communication between card and reader (by using MIFARE Classic CSN and Bosch code or Bosch coded DESFire credentials), as well as between reader and AMC2 controller via the OSDP V2 Secure Channel protocol.

The upgrade from the Bosch proximity readers or the LECTUS duo classic readers to the LECTUS duo DESFire readers is a simple process. The hardware is compatible between both product lines and with the

same software and hardware of the Bosch portfolio. The LECTUS duo reader series operates with low-current consumption, from 8 to 16 volts, and has the same hardware interfaces.

The rugged polycarbonate housing is designed to withstand severe outdoor conditions and provides reliable performance and resistance to vandalism, with IP65 and IK08 (IK10) ratings.

### Technical specifications

#### Electrical

Input voltage	8.5 V to 16 Vdc
Current draw	65 mA @ 12 Vdc Max.: 130 mA @ 12 Vdc

#### Operational

Tamper	Optical Technology
Optical indication	LED, red, yellow, green
Audible indication	Buzzer
Reader interfaces	RS485, Wiegand
Reader protocols	OSDP V2 SC, Wiegand
Keypad	LECTUS duo 3000 C: none LECTUS duo 3000 CK: 2x6

#### Environmental

Operating environment	Indoor and outdoor use - all weather.
Operating temperature	-25 °C to 65 °C (-13 °F to 150 °F)
Operating humidity	0 to 95% (Non-condensing)
IP rating	IP65
UV-light resistant	Yes
Vandal resistance	LECTUS duo 3000 C: IK08 LECTUS duo 3000 CK: IK10

#### MIFARE & Cards specification

Read range - ISO cards	> 6 cm (2.36 in.)
Key fob	> 2 cm (0.78 in.)

Supported cards	MIFARE classic (ISO 14443A CSN/Bosch code)
Anti-collision support	Yes
<b>Mechanical</b>	
Dimensions (L x W x D)	137 mm x 44 mm x 27.5 mm (approx. 5.39 in. x 1.73 in. x 1.08 in.)
Weight	Approx. 220 g (0.5 lb)

### Ordering information

#### ARD-AYBS6260 Card reader, MIFAREclassic

Proximity reader supporting data record of Bosch coded MIFARE classic cards and keyfobs and CSN of ISO14443A credentials, providing RS485/OSDP and Wiegand interface on same device, IP65 rated for indoor and outdoor use, for mullion mount.

Order number **ARD-AYBS6260 | F.01U.166.055**

#### ARD-AYBS6360 Card reader with keypad, MIFAREclassic

Proximity reader supporting data record of Bosch coded MIFARE classic cards and keyfobs and CSN of ISO14443A credentials, providing RS485/OSDP and Wiegand interface on same device, IP65 rated for indoor and outdoor use, for mullion mount, 2x6 keypad.

Order number **ARD-AYBS6360 | F.01U.166.056**

#### Represented by:

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
emea.securitysystems@bosch.com  
emea.boschsecurity.com

**Germany:**  
Bosch Sicherheitssysteme GmbH  
Robert-Bosch-Ring 5  
85630 Grasbrunn  
Germany  
www.boschsecurity.com

**North America:**  
Bosch Security Systems, LLC  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
onlinehelp@us.bosch.com  
www.boschsecurity.us

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia