


IR MOTORIZED VF VANDAL-PROOF DOME CAMERA

DAI+250IP5MVF



1/2.5" CMOS Sensor	ONVIF	3.3-12mm Motorized Vari-Focal Lens	I/O – 1 Alarm in / 1 Alarm Out
5 Mega-Pixel	True WDR / BLC / HLC	25m IR Illumination	2 Way Audio
True Day & Night (IR Cut Removable)	3D Noise Reduction	PoE Support	Technician Port
H.265 (HEVC) Compression	Motion Detection and Privacy Masking	Local Storage	IP 66 Protection
0 Lux (IR On) Min. Illumination	Analytics Support	RS-485	IK 10 Vandal-Proof

Specifications

Camera		Model	
Video	Image Sensor	DAI+250IP5MVF	
	Effective Pixels	1/2.5" CMOS (4:3)	
	Electronic Shutter	2592x1944	
	Frame Rate	1/25s ~ 1/100000s	
	Day & Night	1-25/30 (With True-WDR)	
	Min. Illumination	ICR	
	Audio compression	Day: 0.036lux / Night: 0.009lux (@F2.0, AGC On) 0lux with IR on	
	Communication	G.711A/G.711U	
	Image Settings	Two-way Audio	
	Image Enhancement	AWB, AGC Adjustable, Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable	
Noise Reduction	True WDR (120dB, HFR* Disabled) / BLC / HLC / ROI		
Image Orientation	3D-DNR		
Privacy Zone	Mirror/Flip		
Motion Detection	Yes		
Analytics	Yes		
Video Compression	Camera Tampering, Line Crossing, Sterile Area, Object Monitoring, People Gathering/Intrusion/Counting, Smart Search, Face Detection		
Resolution	H.265 / H.264 / MJPEG*		
Multi-Stream	5MP(2592x1944), 4MP(2560x1440), 1080P, 720P, D1, CIF, 480x240		
Bit rate	5MP / 4MP / 1920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS)		
Encode Mode	64Kbps ~ 8Mbps@H.265 / 128Kbps ~ 10Mbps@H.264		
Image Quality	VBR/CBR		
	Five levels under VBR; Free adjustment under CBR		
Housing	IR Distance	25m (30 IR LED)	
	Lens (Field of View)	3.3-12mm Motorized with Auto-Focus (97.5°-38.5°)	
	Iris	Fixed Iris	
	Lens Mount	Φ14 mount	
	Protection Rate	Water Proof: IP66 / Vandal Proof: IK10	
	Bracket	3-Axis Gimbal	
	Dimensions	Φ150mm×114mm	
	Weight(gross)	880g	
	Network	RJ45 (+PoE)	
	Power	DC Socket	
Analog Video Output	CVBS(BNCx1)		
Audio Connectivity	1Ch Input, 1Ch Output		
SD Card	Support Event recording over TF (128GB Max)		
RS485	Yes		
Alarm	1Ch Input, 1Ch Output		
Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App		
User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission		
Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP		
ONVIF	Yes		
Ethernet	100Mbps		
PoE	Yes		
Power Supply	DC12V/~360mA / PoE/~6.2W		
Work Environment	-30 C ~ 50 C, 10%~90% Humidity		

