

DT2063N

Detector analógico térmico con salida de piloto remoto. Serie 2000.

General

The DT2063N is a 2000 series protocol, addressable heat detector certified to class A2R. It provides good looks as well as top features, including a rate-of-rise algorithm that allows the device to raise the alarm before the fixed temperature trigger point is reached. Dual fire LEDs indicate an alarm visible from all directions, eliminating the need for special detector orientation on installation, whilst a remote indicator output is provided as standard on every device.

Installation friendly

The DT2063N is individually identified by setting an address through two rotary switches. The address is a straight numerical value and does not require binary or hexadecimal conversions, significantly reducing the risk of incorrect addressing.

All 2000 series detectors are compatible with a standard base that makes them easily interchangeable.

State of the art communication

Panel to device communication is provided through a powerful SIA protocol featuring multiple bus cycle codes and CRC error checking and ensuring reliable communications between the device and the control panel.

This enhanced protocol ensures the overall integrity and error free operation of the full system, without compromising speed.

Extended applications

For varied applications the fixed temperature trigger level of the DT2063N may be set from the CIE to accommodate higher activation temperatures.

A comprehensive line of complimentary devices completes the 2000 series portfolio:

- common use detector bases
- optical, temperature and multi-sensors
- standalone and base isolators
- sounder circuit controllers
- conventional zone monitoring units
- various supervised and non-supervised I/O units
- a comprehensive line of manual call points
- loop powered notification devices and beam detectors



Detalles

- Dual thermistors
- Remote signaling capabilities
- Easy numeric addressing (1-128)
- Enhanced communication protocol
- Full diagnostic self testing
- Full range including optical and multi sensors
- Full range of I/O units and accessories
- Optional isolator base
- EN54:5 approved and CPR certified

DT2063N

Detector analógico térmico con salida de piloto remoto. Serie 2000.

Especificaciones técnicas

General

Indicación de estado	Dual red alarm LED
User interface	LEDs
Compatibilidad	Aritech 2000 series systems
Alarm levels	5
Conectividad	2000 Series bases

Eléctrico

Voltaje de funcionamiento	17 to 28 VDC
Consumo de corriente	<270 μ A (quiescent at 24 VDC) 4.7 mA (alarm at 24 VDC)

Detección

Principio de detección	Heat
Supervisión	Alarm threshold
Sensibilidad	Configurable
Coverage area	<80 m ²
Velocidad del aire	Unaffected
Temperatura de alarma	> +40°C
Tasa de aumento	Class A2

Salida

Cantidad de salidas	1
Ratio y tipo de salida	Remote indicator
Programable	No
Salida de alarma remota	4.7 mA

Físico

Physical dimensions	100 x 50 mm (Ø x H)
Peso neto	83 g
Color	Blanco nuboso (RAL 9001)
Tipo de Montaje	Montaje en el techo
Material (body)	Plástico

Medioambiental

Antivandálico	No
Operating temperature	-10 to +50°C
Temperatura de almacenamiento	-10 to +70°C
Temperatura ambiente	+25°C
Humedad relativa	10 to 95% noncondensing
Environment	Interior
IP rating	IP20

Regulador

Cumplimiento	CE, REACH, RoHS 3, WEEE
Certificación	CPR
Normativas	EN54-5

Productos compatibles

Categoría	Referencia	Descripción
Dispositivo de detección	DB2002	Base de conexiones Serie 2000 de 100mm de diámetro.
Dispositivo de detección	DB2002U	Base de conexiones Serie 2000 de 150mm de diámetro con.
Dispositivo de detección	DB2004	Base profunda de conexiones Serie 2000 de 10 cm de diámetro con 5 Terminales.
Dispositivo de detección	DB2016	Base con aislador serie 2000.
Dispositivo de notificación	AI672	Piloto indicador de acción convencional para detectores de incendio de las series Dx700/Dx2000..
Dispositivo de notificación	AI673	Piloto indicador de acción acústico convencional para detectores de incendio de las series Dx700/Dx2000.
Dispositivo de notificación	DB2368IAS-W	Base con sirena direccionable alimentada de lazo serie 2000 con aislador. Blanca.



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.