


# 80M IR MOTORIZED VF BULLET CAMERA

I8-340IP5MVF+



- |                                     |                                       |                                |                  |
|-------------------------------------|---------------------------------------|--------------------------------|------------------|
| 1/3" CMOS Sensor                    | ONVIF                                 | 80m IR Illumination            | 2 Way Audio      |
| 4 Mega-Pixel                        | True WDR / BLC / HLC                  | PoE Support                    | CVBS             |
| True Day & Night (IR Cut Removable) | 3D Noise Reduction                    | Local Storage                  | Technician Port  |
| H.265 (HEVC) Compression            | Motion Detection and Privacy Masking  | RS-485                         | IP 66 Protection |
| 0 Lux (IR On) Min. Illumination     | 9-22mm Motorized Lens with Auto-Focus | I/O – 1 Alarm in / 1 Alarm Out |                  |

## Specifications

Camera	Video	Model	I8-340IP5MVF+
		Image Sensor	1/3" CMOS
		Effective Pixels	2688x1520
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	1-25/30 (With True-WDR)
		Day & Night	ICR
		Min. Illumination	0lux (IR ON)
	Audio	Audio compression	G.711A/G.711U
		Communication	Two-Way Audio
	Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
Image Enhancement		True WDR / BLC / HLC / ROI	
Noise Reduction		3D-DNR	
Image Orientation		Mirror/Flip	
Privacy Zone		Yes	
Motion Detection		Yes	
Compression	Video Compression	H.265 / H.264	
	Resolution	4MP(2560x1440), 3MP(2048x1536), 1080P, 720P, D1, CIF, 480x240	
	Multi-stream	4MP / 3MP / 1920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS)	
	Bit rate	64Kbps ~ 7Mbps@H.265 / 128Kbps ~ 9Mbps@H.264	
	Encode Mode	VBR/CBR	
Image Quality	Five levels under VBR; Free adjustment under CBR		

Housing	IR Distance	80m (4 IR LED Array)
	Lens	9-22mm Motorized with Auto-Focus
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66
	Bracket	3-Axis
	Dimensions	Φ109mm×284mm
Connectivity	Weight(gross)	1700g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	CVBS(BNCx1)
	Mic Connectivity	1Ch Input, 1Ch Output
	SD Card	Support Event Recording over SD (128GB Max)
	RS485	Yes
Network	Alarm	1Ch Input, 1Ch Output
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP
	ONVIF	Yes
	Ethernet	100Mbps
	PoE	Yes
Others	Power Supply	DC12V/~980mA / PoE/~14W
	Work Environment	-30 C ~50 C , 10%~90% Humidity

