

DHL19-F600

19.5" Monitor



Features :

- Industrial level LCD panel, suitable for continuous 24/7 operation
- High fidelity digital processing for a brilliant and vivid video
- 5ms fast response time for no motion blur, judder or ghosting
- Low energy consumption, long service life



Technical Specification

Model

| | |
|-------|------------|
| Model | DHL19-F600 |
|-------|------------|

Display

| | |
|----------------------|-----------------|
| Screen Size | 19.5" |
| Aspect Ratio | 16:9 |
| Resolution | 1600×900 |
| Backlight | LED |
| Brightness/Luminance | 200 cd/㎡ |
| Contrast Ratio | 1000:1 |
| Display Color | 16.7M(8bit) |
| Viewing Angle(H/V) | 170°(H)/160°(V) |
| Response Time | 5ms |
| Refresh Rate | 60Hz |

Signals

| | |
|-------|--------------|
| Input | VGA(D-Sub)×1 |
|-------|--------------|

General

| | |
|------------------------|----------------------|
| Power Supply | AC110~240V, 50/60 Hz |
| Consumption (Standard) | 25W |
| Consumption (Standby) | ≤0.5W |

| | | |
|--------------------------------|---------------------------------------|-----------------------|
| Type | Internal | |
| Net Weight | 3.8kg (8.4lb) | |
| Gross Weight | 4.8kg (10.6lb) | |
| Bezel Width | 16.7mm (U/R/L), 25mm (B) | |
| VESA | 75×75mm (3.0"×3.0") | |
| Dimension without base (W×H×D) | 467.0×283.0×51.5mm (18.4"×11.1"×2.0") | |
| Package(W×H×D) | 533×410×115mm (21.0"×16.1"×4.5") | |
| Work Environment | Temperature | 0°C~40°C (32°F~104°F) |
| | Humidity | 10%~85% |

Accessory

| | |
|----------|----------------------------------|
| Standard | VGA cable, power cable, pedestal |
| Optional | Hanging bracket |

Certifications

| | |
|----------------|--------|
| Certifications | CE/FCC |
|----------------|--------|

Dimensions(mm)

