

# IR FIXED LENS VANDAL-PROOF MINI DOME CAMERA

DMA-340IP528+  
DMA-340IP536+



- |                                     |                                      |                           |                     |
|-------------------------------------|--------------------------------------|---------------------------|---------------------|
| 1/3" CMOS Sensor                    | ONVIF                                | 2.8/3.6mm Mega-Pixel Lens | 1 Way Audio         |
| 4 Mega-Pixel                        | True WDR / BLC / HLC                 | 10m IR Illumination       | Built-In Microphone |
| True Day & Night (IR Cut Removable) | 3D Noise Reduction                   | PoE Support               | CVBS                |
| H.265 (HEVC) Compression            | Motion Detection and Privacy Masking | 1 Way Audio               | IK 10 Vandal Proof  |
| 0 Lux (IR On) Min. Illumination     | Analytics Support                    | Local Storage             |                     |

## Specifications

Camera	Model	DMA-340IP528	DMA-340IP536
		Video	Image Sensor
	Effective Pixels	2688x1520	
	Electronic Shutter	1/25s ~ 1/100000s	
	Frame Rate	Standard: 1-25/30 (True-WDR), HFR*: 1-50/60 (Max. 1080P & D-WDR)	
	Day & Night	ICR	
	Min. Illumination	Day: 0.045lux / Night: 0.01lux (@F1.8, AGC On) 0lux with IR on	
Audio	Audio compression	G.711A/G.711U	
	Communication	One-way Audio	
Image Processing	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable	
	Image Enhancement	True WDR (120dB, HFR* Disabled) / BLC / HLC / ROI	
	Noise Reduction	3D-DNR	
	Image Orientation	Mirror/Flip	
	Privacy Zone	Yes	
	Motion Detection	Yes	
	Analytics	Pro Level	
Compression	Video Compression	H.265 / H.264	
	Resolution	4MP(2560x1440), 3MP(2048x1536), 1080P, 720P, D1, CIF, 480x240	
	Multi-Stream	4MP / 3MP / 1920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS / 1~50/60FPS with HFR*)	
	Bit rate	64Kbps ~ 7Mbps@H.265 / 128Kbps ~ 9Mbps@H.264	
	Encode Mode	VBR/CBR	
Image Quality	Five levels under VBR; Free adjustment under CBR		

Housing	IR Distance	10m (12 IR LED)	
	Lens (Field of View)	2.8mm (107°)	3.6mm (71°)
Iris	Fixed Iris		
Lens Mount	Φ14 mount		
Protection Rate	Vandal Proof: IK10		
Bracket	3-Axis Gimbal		
Dimensions	Φ110mm×57.8mm		
Weight(gross)	350g		
Connectivity	Network	RJ45 (+PoE)	
	Power	DC Socket	
	Analog Video Output	CVBS (BNCx1)	
	Mic Connectivity	Built-In Microphone + Mic Input	
	SD Card	Support recording over TF (128GB Max)	
	RS485	No	
Network	Alarm	No	
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App	
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission	
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1X, Multicast, QoS	
Others	ONVIF	Yes	
	Ethernet	100Mbps	
PoE	Yes		
Power Supply	DC12V/~340mA / PoE/~4.7W		
Work Environment	-30°C~50°C, 10%~90% Humidity		

\*HFR (High Frame Rate) must be supported by the NVR in order to work properly.

