

FE160MS

Cerradura electromagnética de 6.000N monitorizado, para montaje de superficie.

Description

Eco Line magnetic lock, 600 Kgf, monitored, surface mounting

Application

High security applications for internal and external doors. To be mounted inside external doors.

Reliable Security

This state of the art electro-magnetic locking device provides positive, instantaneous door control. Filler plates, angle brackets, and other mounting adapters are available to satisfy a wide range of door and frame types and conditions.

Safe operation

Our locking devices are inherently fail-safe, releasing instantly upon command or loss of power. With no moving parts to wear, stick or bind; no mechanical linkages to bend or break; and no bolt travel time or misalignment to raise concern, both unlocking and locking are always accomplished with ease and efficiency. As those electromagnetic locking devices function independently of any mechanical type locks, magnetic locks will not jeopardize the fire door rating of an opening.



Detalles

- 600 Kgf holding power
- Surface mounted
- No residual magnetism
- 12/24 V dc jumper selectable operation
- Monitored changeover
- Mounts easily with a minimum of tools

FE160MS

Cerradura electromagnética de 6.000N monitorizado, para montaje de superficie.

Especificaciones técnicas

General

Tipo de producto	Cerradura magnética
------------------	---------------------

Fuerza de retención

Fuerza de retención kgf (kilogramos de fuerza)	600 kgf
--	---------

Fuerza de retención N (Newtons)	6000
---------------------------------	------

Monitorización y estado

Supervisado	Si
-------------	----

Indicador LED	Si
---------------	----

Interruptor de estado de la puerta	No
------------------------------------	----

Cambio monitorizado	Si
---------------------	----

Sensor de enlace magnético	Si
----------------------------	----

Eléctrico

Valor de la fuente de alimentación	12 / 24 VDC
------------------------------------	-------------

Consumo de corriente	450 mA (+/- 2,5% @ 13,5 V)
----------------------	----------------------------

Físico

Dimensiones físicas	266 x 73 x 40 mm (W x H x D)
---------------------	------------------------------

Color	Aluminio
-------	----------



Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 5 May 2023 - 9:32