

FE235

Retenedor electromagnético, 400 N, para montaje en superficie

General

The FE235 is a surface mount door holder, with a Bayblend base, which offers a 400N holding force.

Magnet construction

The magnet is constructed with a pressed coil and anti-remenance pin, giving it a protection of IP54. The protection diodes are integrated into this construction.

Housing

The plastic base is manufactured from Bayblend and contains 30% PA6 glass fiber, which makes it much stronger than standard ABS. Bayblend offers high heat resistance, high impact and notched impact strength, and high stiffness and dimensional stability.

Installer friendly

- For practical ease of installation, the door holder comes complete with electrical screw terminals.
- The base is predrilled in a practical, standard format for rapid mounting.
- The door holder is supplied complete with a keeper plate, which offer angular adjustment.

Approvals

The FE235 is fully approved according to EN1155.



Detalles

- Low power - 1.6 W
- 400 N holding force
- Anti-remnant ejector
- Spark suppression diode and reverse polarity protection
- EN1155 approved
- Keeper plate included

FE235

Retenedor electromagnético, 400 N, para montaje en superficie

Especificaciones técnicas

General

Fuerza de retención N (Newtons) 400

Botón de liberación No

Diodo de supresión de chispa Yes

Protección contra inversión de polaridad Yes

Eléctrico

Tipo de fuente de alimentación 24 VCC

Consumo de corriente 1.6 W

Ciclo de trabajo 100%

Físico

Dimensiones físicas 55 x 55 x 33 mm

Medioambiental

Clasificación IP IP54 (magnet)
IP42 (connection)

Regulador

Normativas EN1155

Productos compatibles

Categoría	Referencia	Descripción
Retenedores	FE225-150	Soporte para montaje en pared o suelo para la serie FE200. Longitud 150mm.
Retenedores	FE225-300	Soporte para montaje en pared o suelo para la serie FE200. Longitud 300mm.
Retenedores	FE527	Base cuadrada estándar de acero. Dimensiones: 55x18mm.
Retenedores	FE529	Base cuadrada estándar de acero. Eslabón giratorio de 120 grados. Dimensiones: 55x50mm.



Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 23 October 2024 - 11:47