

VVS302-PLUS

Seismic detector for ATM's and night deposit boxes, NC contact

Superior detection

The VVS3xx-PLUS series seismic detectors are designed to detect attempts to break into vaults, safes, night deposit boxes, automatic teller machines (ATM's) and other reinforced physical areas such as data storage's and filing cabinets. These seismic detectors react to the characteristic vibration patterns of all breaking-and-entering tools, such as hammers, drills, diamond saws, hydraulic pressure tools and thermal tools like welding torch and thermal lance. They sense vibrations that occur within a 3 to 14 meter radius of where they are mounted, depending on the material and design of the protected object.

Excellent false alarm immunity

At the same time the seismic detectors allow for normal human activity around the protected area without the risk of creating unwanted alarms. To achieve this high level of accuracy, each detector features "three detectors in one". All three channels (counting, integration, and explosion) analyze the signal frequencies, duration and amplitude, in order to differentiate between random environmental disturbances and real intruder attack. The end result is detectors with excellent detection and false alarm immunity.

Testing & accessories

The VVS3xx-PLUS series provides two different test functions: automatic or manual activated. You can choose between an internal test of the detector electronics or, by using the test transmitter VVT705, do a functional test of the detector and its physical contact to the protected object. A complete range of accessories is provided for all kinds of applications to achieve the highest security.



Details

- Detects all known types of attack
- Advanced signal processing differentiates between ambient noise and real attacks
- Protects any solid structure
- Remote test capability
- Adjustable sensitivity
- Advanced tamper protection
- Complete line of accessories
- Easy to install

VVS302-PLUS

Seismic detector for ATM's and night deposit boxes, NC contact

Technical specifications

General

Tipo de aplicación	Cajero (ATM), Cajas fuertes nocturnas
Protección de tamper	Temperature 84°C, drill shield, opening contact, pry-off contact
Indicación de alarma	LED-Tornillo de indicación no. 3
Alarma de tensión baja	7,5 V

Detection

Rango	Radio de 3 a 14 m
Ajuste de sensibilidad	5 pasos de aprox. 6 dB cada uno

Inputs/outputs

Contacto de alarma	NC
Salida de prueba	Yes

Electrical

Valor de la fuente de alimentación	9 to 15 VDC, 2 V max ripple ptp
Consumo de corriente	8.6 mA (nominal)

Physical

Dimensiones físicas	81 x 101 x 28 mm (L x W x H)
Peso neto	380 g
Color	Gris (RAL 7035)

Environmental

Temperatura de funcionamiento	-20 to +55°C
Humedad relativa	0 to 90% noncondensing at 30°C
Clasificación IP	IP30

Test output

	Analog output (terminal 4)
--	----------------------------



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 5 May 2023 - 9:33