

Remote indicator for Series 9000, 9200 and IQ8Quad, red lens



Part-No.: 781814


Red prism is continuously or pulsed illuminated by 3 LEDs. Connection by 2-wire cable to detector base.

Common technical data

Operating voltage	1,8 ... 3 V DC
Current consumption	approx. 9 mA
Alarm display	3 red LEDs
Ambient temperature	-25 °C ... 70 °C
Storage temperature	-35 °C ... 85 °C
Air humidity	< 95 %
Type of protection	IP 42
Housing	ABS plastic
Color	white, similar to RAL 9010
Weight	approx. 60 g
Dimensions	W: 85 mm H: 82 mm D: 27 mm

Features:

- Viewing angle 180°
- Default activation by a connected detector
- Configurable activation by any system event programmable via tools 8000 software

 Detectors Series 9000 Standard detector base Part No. 781590 and adapter module Part No. 781487 required Max. 2 detectors per indicator / max. 2 indicators per detector Remote indicator is lit continuously when activated
Detectors Series ES Detect Detector base 805590 required for Series ES Detect Max. 3 detectors per indicator / max. 3 remote indicators per detector Indicator flashes when activated (Pulse frequency approx.1 Hz)
Detectors Series 9200/IQ8Quad / ES Detect Standard detector base Part No. 781590 or base Part No. 801593 required for Series 9200 detectors Standard base Part No. 805590 required for Series IQ8Quad Max. 1 remote indicator per detector Max. 60 remote indicators per zone (with max. 30 detectors) Indicator flashes when activated (Pulse frequency approx.1 Hz)