

# IRIS Printer

- Thermal printer in a metal box
- Suitable for modular structure
- Self test and status indication



## DESCRIPTION:

The IRIS Printer is a heat printer specially designed for connection to IRIS PRO, iRIS8 and iRIS8 Big Box analogue-addressable fire alarm panels. The printer is suitable for building of modular structures with IRIS PRO, iRIS8, iRIS8 Big Box and IRIS PS72 – back-up power supply unit.

IRIS Printer is used for printing of events list and is equipped with independent own power supply.

## FEATURES

- Thermal printer in a metal box
- Suitable for modular structure
- Self test and status indication
- Printing method – direct thermal
- Print density: 8 dots/mm, 576 dots/line
- Print speed: max 170mm/sec
- Two type of fonts supported: 12x24 dots and 9x17 dots

## TECHNICAL SPECIFICATIONS

- Power Supply.....100-240VAC, 3A
- Serial interface.....RS-232C to IRIS PRO
- Paper width.....80mm, valid print width 72mm
- Print speed max..... 170mm/sec
- Operating temperature.....-10°C to +50°C
- Color.....Grey
- Dimensions.....430x330x117mm

## COMPATIBLE PRODUCT RANGE

- IRIS PRO, iRIS8, iRIS8 Big Box analogue-addressable fire alarm panels
- IRIS PRO FLM kit

Last update: 04.2021