



EMC TEST REPORT

Authorized under Declaration of Conformity

According to

EN 55032: 2012+AC 2013 (Class B)	EN 55024 : 2010
EN 61000-3-2 : 2014	EN 50130-4: 2011
EN 61000-3-3 : 2013	IEC 61000-4-2 : 2008
	IEC 61000-4-3 : 2006+A1:2007+A2:2010
	IEC 61000-4-4 : 2012
	IEC 61000-4-5 : 2014
	IEC 61000-4-6 : 2013
	IEC 61000-4-8 : 2009
	IEC 61000-4-11 : 2004

Applicant : Zhejiang Dahua Vision Technology Co., Ltd.
Address : No.1199, Bin'an Road, Binjiang District, Hangzhou, P.R.
China
Equipment : NETWORK VIDEO RECORDER
DHI-NVR4208-4KS2, DHI-NVR4216-4KS2,
DHI-NVR4232-4KS2, NVR4208-4KS2,
Model No. : NVR4216-4KS2, NVR4232-4KS2,
NVR2204-4KS2, NVR2208-4KS2,
DHI-NVR2204-4KS2, DHI-NVR2208-4KS2,
HS602-J1900-2G, DHI-HS602-J1900-2G
Trade mark : 

I HEREBY CERTIFY THAT :

The sample was received on Nov 05, 2016 and the testing was carried out on Nov 26, 2016 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.



EMC TEST REPORT

Issued by:

Cerpass Technology (Suzhou) Co.,Ltd

No.66,Tangzhuang Road, Suzhou Industrial Park, Jiangsu 215006, China

Tel:86-512-6917-5888

Fax:86-512-6917-5666

The test record, data evaluation & Equipment Under Test configurations represented herein are true and accurate accounts of the measurements of the samples EMC characteristics under the conditions specified in this report.

The above equipment was tested by Cerpass Technology Corp. for compliance with the requirements of technical standards specified above under the EMC Directive **2014/30/EU**. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties

Approved by:

Miro Chueh
EMC/RF B.U. Manager

Laboratory Accreditation:

Cerpass Technology Corporation Test Laboratory

NVLAP LAB Code:	200954-0
TAF LAB Code:	1439

Cerpass Technology(SuZhou) Co., Ltd.

NVLAP LAB Code:	200814-0
CNAS LAB Code:	L5515



Contents

1. Summary of Test Procedure and Test Results	6
2. Immunity Testing Performance Criteria Definition	7
3. Test Configuration of Equipment under Test	8
3.1. Feature of Equipment under Test	8
3.2. Test Manner	9
3.3. Description of Support Unit	10
3.4. General Information of Test	11
3.5. Measurement Uncertainty	12
4. Test of Conducted Emission	14
4.1. Test Limit	14
4.2. Test Procedures	17
4.3. Typical Test Setup	17
4.4. Measurement Equipment	18
4.5. Test Result and Data	19
4.6. Test Photographs of Power Port	25
4.7. Test Photographs of Telecommunication Port	26
5. Test of Radiated Emission	27
5.1. Test Limit	27
5.2. Test Procedures	30
5.3. Typical Test Setup	30
5.4. Measurement Equipment	31
5.5. Test Result and Data (30MHz ~ 1GHz)	32
5.6. Test Result and Data (1GHz ~ 6GHz)	36
5.7. Test Photographs (30MHz~1GHz)	40
5.8. Test Photographs (1GHz~6GHz)	41
6. Harmonics Test	42
6.1. Limits of Harmonics Current Measurement	42
6.2. Measurement equipment	43
6.3. Test Result and Data	44
6.1. Test Photographs	46
7. Voltage Fluctuations Test	47
7.1. Test Procedure	47
7.2. Measurement Equipment	47
7.3. Test Result and Data	48
7.4. Test Photographs	50
8. Electrostatic Discharge Immunity Test	51
8.1. Test Procedure	51
8.2. Test Setup for Tests Performed in Laboratory	52
8.3. Test Severity Levels	53
8.4. Measurement Equipment	53
8.5. Test Result and Data	54
8.6. Test Photographs	56
9. Radio Frequency electromagnetic field immunity test	60



- 9.1. Test Procedure 60
- 9.2. Test Severity Levels 60
- 9.3. TEST SETUP 61
- 9.4. Measurement Equipment 62
- 9.5. Test Result and Data 63
- 9.6. Test Photographs 65
- 10. Electrical Fast Transient/ Burst Immunity Test 66**
 - 10.1. Test Procedure 66
 - 10.2. Test Severity Levels 66
 - 10.3. TEST SETUP 67
 - 10.4. Measurement Equipment 68
 - 10.5. Test Result and Data 69
 - 10.6. Test Photographs 72
- 11. Surge Immunity Test 73**
 - 11.1. Test Procedure 73
 - 11.2. Test Severity Level 73
 - 11.3. TEST SETUP 74
 - 11.4. Measurement Equipment 74
 - 11.5. Test Result and Data 75
 - 11.6. Test Photographs 79
- 12. Conduction Disturbances induced by Radio-Frequency Fields 80**
 - 12.1. Test Procedure 80
 - 12.2. Test Severity Levels 80
 - 12.3. TEST SETUP 81
 - 12.4. Measurement Equipment 81
 - 12.5. Test Result and Data 82
 - 12.6. Test Photographs 84
- 13. Power Frequency Magnetic Field Immunity Test 85**
 - 13.1. Test Setup 85
 - 13.2. Test Severity Levels 85
 - 13.3. Measurement Equipment 85
 - 13.4. Test Result and Data 86
 - 13.5. Test Photographs 87
- 14. Voltage Dips and Voltage Interruptions Immunity Test Setup 88**
 - 14.1. Test Conditions 88
 - 14.2. TEST SETUP 88
 - 14.3. Measurement Equipment 88
 - 14.4. Test Result and Data 89
 - 14.5. Test Photographs 92
- 15. EUT Photographs 93**



1. Summary of Test Procedure and Test Results

EMISSION[EN 55032: 2012+AC 2013]			
Standard	Item	Result	Remarks
EN 55032: 2012+AC 2013	Conducted (Power Port)	PASS	Meets Class B Limit Minimum passing margin(AV) is -14.63 dB at 12.8979 MHz
	Conducted (Telecom port)	PASS	Meets Class B Limit Minimum passing margin(AV) is -4.47 dB at 0.5580 MHz
	Radiated	PASS	Meets Class B Limit Minimum passing margin(QP) is -3.88 dB at 933.0700 MHz
EN 61000-3-2: 2014	Harmonic current emissions	PASS	Meet Class A Limit
EN61000-3-3:2013	Voltage fluctuations & flicker	PASS	Meets the requirements

IMMUNITY[EN 55024:2010]			
Standard	Item	Result	Remarks
IEC 61000-4-2: 2008	ESD	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-3: 2006+A1:2007+A2:2010	RS	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-4: 2012	EFT	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-5:2014	Surge	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-6:2013	CS	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-8:2009	PFMF	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-11:2004	Voltage dips & voltage variations	PASS	Meets the requirements of Voltage Dips: 1) >95% reduction Performance Criterion B 2) 30% reduction Performance Criterion B Voltage Interruptions: 1) >95% reduction Performance Criterion C



IMMUNITY[EN 50130-4: 2011]			
Standard	Item	Result	Remarks
IEC 61000-4-2: 2008	ESD	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-3: 2006+A1:2007+A2:2010	RS	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-4: 2012	EFT	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-5:2014	Surge	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-6:2013	CS	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-11:2004	Voltage dips & voltage variations	PASS	Meets the requirements of Voltage Dips: 1) 60% reduction Performance Criterion A 2) 30% reduction Performance Criterion A 3) 20% reduction Performance Criterion A Voltage Interruptions: 1) 100% reduction Performance Criterion A

2. Immunity Testing Performance Criteria Definition

- A. Normal performance within limits specified by the manufacture, requestor or purchaser;
- B. Temporary loss of function or degradation of performance which ceases after the disturbance ceases, and from which the equipment under test recovers its normal performance, without operator intervention;
- C. Temporary loss of function or degradation of performance, the correction of which requires operation intervention;
- D. Loss of function or degradation of performance which is not recoverable, owing to damage to hardware or software, or loss of data.



3. Test Configuration of Equipment under Test

3.1. Feature of Equipment under Test

First edition:

NETWORK VIDEO RECORDER	Model No.:	DHI-NVR4208-4KS2, DHI-NVR4216-4KS2, DHI-NVR4232-4KS2, NVR4208-4KS2, NVR4216-4KS2, NVR4232-4KS2, NVR2204-4KS2, NVR2208-4KS2, DHI-NVR2204-4KS2, DHI-NVR2208-4KS2, HS602-J1900-2G, DHI-HS602-J1900-2G
Remark	<p>DHI-NVR4232-4KS2 was selected as the test model and its data have been recorded in this report.</p> <p>These models are similar except model name.</p> <p>The new models and initial models are similar except for model name and market purpose.</p>	
Adapter	Model No.:	DPS-48DB
	Input:	100V-240V~/1.2A, 50Hz-60Hz
	Output:	12V,4A

Note: Please refer to user manual.

Original:

NETWORK VIDEO RECORDER	Model No.:	DHI-NVR4208-4KS2,DHI-NVR4216-4KS2, DHI-NVR4232-4KS2,NVR4208-4KS2, NVR4216-4KS2,NVR4232-4KS2
Remark	<p>DHI-NVR4232-4KS2 was selected as the test model and its data have been recorded in this report.</p> <p>These models are similar except model name.</p>	
Adapter	Model No.:	DPS-48DB
	Input:	100V-240V~/1.2A, 50Hz-60Hz
	Output:	12V,4A

Note: Please refer to user manual.



3.2. Test Manner

Test Manner

- a During testing, the interface cables and equipment positions were varied according to Europe Standard.
- b Turn on the power of all equipment.
- c The complete test system included Notebook PC, HDD, USB Mouse, LCD Monitor, DVD, Sound and EUT for EMC test.

The pre-test modes(CE/RE)

- Mode 1 Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(110V/60Hz)
Mode 2 Full System(VGA Mode:1280*1024@60Hz + HDMI Mode:1280*1024@60Hz) (110V/60Hz)
Mode 3 Full System(VGA Mode:1280*720@60Hz + HDMI Mode:1280*720@60Hz) (110V/60Hz)
Mode 4 Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(230V/50Hz)

Select the worst case of the pre-test modes as the final test mode(CE/RE)

- Mode 1 Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(110V/60Hz)
Mode 4 Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(230V/50Hz)

The pre-test modes(EMS/H&F)

- Mode 1 Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)
Mode 2 Full System(VGA Mode:1280*1024@60Hz + HDMI Mode:1280*1024@60Hz)
Mode 3 Full System(VGA Mode:1280*720@60Hz + HDMI Mode:1280*720@60Hz)

Select the worst case of the pre-test modes as the final test mode(EMS/H&F)

- Mode 1 Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)

The pre-test modes(ISN)

- Mode 1 Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(LAN 100M)
(110V/60Hz)
Mode 2 Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz) (LAN 100M)
(230V/50Hz)

Select the worst case of the pre-test modes as the final test mode(ISN)

- Mode 1 Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(LAN 100M)
(110V/60Hz)
Mode 2 Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz) (LAN 100M)
(230V/50Hz)



3.3. Description of Support Unit

No.	Device	Manufacturer	Model No.	Description
1	Notebook PC	SONY	PCG-71811P	Non-Shielded,1.8m (R33021)
2	HDD	WD	N/A	N/A
3	USB Mouse	DAHUA	M17-601USB	N/A
4	LCD Monitor	DELL	U2713HMt	Non-Shielded, 1.8m
5	LCD Monitor	DELL	SE198WFPT	Non-Shielded,1.8m(R433 46)
6	DVD	PIONEER	DV-600AV	Non-Shielded,1.5m
7	Sound	EACAN	A-600IIR	Non-Shielded,1.8m

No.	Cable	Quantity	Description
A	USB Cable	1	Shielded, 0.6m
B	USB Cable	1	Shielded,1.2m
C	VGA Cable	1	Shielded, 1.8m,with two ferrite core bonded
D	HDMI Cable	1	Shielded, 1.8m
E	LAN Cable	1	Non-Shielded, >3.0m
F	Audio in Cable	1	Non-Shielded, 1.8m
G	Audio out Cable	1	Non-Shielded, 1.8m



3.4. General Information of Test

<input type="checkbox"/>	Test Site	<p>Cerpass Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel:+886-3-3226-888 Fax:+886-3-3226-881 Address: No.68-1, Shihbachongsi, Shihding Township, New Taipei City 223, Taiwan, R.O.C. Tel: +886-2-2663-8582</p>
	FCC	TW1079, TW1061,390316, 228391, 641184
	IC	4934B-1, 4934E-1, 4934E-2
	VCCI	T-2205 for Telecommunication Test C-4463 for Conducted emission test R-3428, R-4128 for Radiated emission test G-812, G-813 for radiated disturbance above 1GHz
<input checked="" type="checkbox"/>	Test Site	<p>Cerpass Technology (Suzhou) Co.,Ltd Address: No.66,Tangzhuang Road, Suzhou Industrial Park, Jiangsu 215006, China Tel: +86-512-6917-5888 Fax: +86-512-6917-5666</p>
	FCC	331395
	IC	7290A-1, 7290A-2
	VCCI	T-1945 for Telecommunication Test C-2919 for Conducted emission test R-2670 for Radiated emission test G-227 for radiated disturbance above 1GHz
Frequency Range Investigated:		Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 6000MHz
Test Distance :		The test distance of radiated emission below 1GHz from antenna to EUT is 10 M. The test distance of radiated emission above 1GHz from antenna to EUT is 3 M.



3.5. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Uncertainty
Conducted emissions(LINE)	9KHz-30MHz	+/- 0.7738 dB
Conducted emissions(NEUTRAL)	9KHz-30MHz	+/- 0.7886 dB

Measurement	Polarity	Frequency	Uncertainty
Radiated emissions (below 1GHz)	H	30MHz ~ 200MHz	+/- 3.8909dB
		200MHz ~1000MHz	+/- 3.6555dB
	V	30MHz ~ 200MHz	+/- 3.8948dB
		200MHz ~1000MHz	+/- 3.6538dB
Radiated emissions (above 1GHz)	H	1000MHz ~18000MHz	+/- 3.8948 dB
		18000MHz ~40000MHz	+/-3.8844dB
	V	1000MHz ~18000MHz	+/- 3.8906dB
		18000MHz ~40000MHz	+/- 3.8744dB

Measurement	Uncertainty
ESD—Rise time tr	10%
ESD—Peak current Ip	6%
ESD—Current at 30 ns	6%
ESD—Current at 60 ns	6%
ESD- Charging voltage	1%
RS above 1GHz	±2.37dB
RS under 1GHz	±3.83dB
EFT—Rise time tr	4%
EFT—Peak current Ip	4%
EFT—Current	4%
Surge—Rise time tr	4%
Surge—Peak current Ip	4%



Surge—Current	4%
CS-CND	±0.80dB
CS-Clamp	±1.06dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Consistent with industry standard (e.g. CISPR 22: 2008, clause 11, Measurement Uncertainty) determining compliance with the limits shall be base on the results of the compliance measurement. Consequently the measure emissions being less than the maximum allowed emission result in this be a compliant test or passing test.



4. Test of Conducted Emission

4.1. Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 kHz and return leads of the EUT according to the methods defined in European Standard EN 55032.

Table A.8 – Requirements for conducted emissions from the AC mains power ports of Class A equipment

Applicable to				
1. AC mains power ports (3.1.1)				
Table clause	Frequency range MHz	Coupling device (see Table A.7)	Detector type / bandwidth	Class A limits dB(μ V)
A8.1	0,15 – 0,5	AMN	Quasi Peak / 9 kHz	79
	0,5 – 30			73
A8.2	0,15 – 0,5	AMN	Average / 9 kHz	66
	0,5 – 30			60

NOTE Apply A8.1 and A8.2 across the entire frequency range.

Table A.9 – Requirements for conducted emissions from the AC mains power ports of Class B equipment

Applicable to				
1. AC mains power ports (3.1.1)				
Table clause	Frequency range MHz	Coupling device (see Table A.7)	Detector type / bandwidth	Class B limits dB(μ V)
A9.1	0,15 – 0,5	AMN	Quasi Peak / 9 kHz	66 – 56
	0,5 – 5			56
	5 – 30			60
A9.2	0,15 – 0,5	AMN	Average / 9 kHz	56 – 46
	0,5 – 5			46
	5 – 30			50

NOTE Apply A9.1 and A9.2 across the entire frequency range.



Table A.10 – Requirements for asymmetric mode conducted emissions from Class A equipment

Applicable to					
1. wired network ports (3.1.30) 2. optical fibre ports (3.1.24) with metallic shield or tension members 3. antenna ports (3.1.3)					
Table clause	Frequency range MHz	Coupling device (see Table A.7)	Detector type / bandwidth	Class A voltage limits dB(μV)	Class A current limits dB(μA)
A10.1	0,15 – 0,5	AAN	Quasi Peak / 9 kHz	97 – 87	n/a
	0,5 – 30			87	
	0,15 – 0,5	AAN	Average / 9 kHz	84 – 74	
	0,5 – 30			74	
A10.2	0,15 – 0,5	CVP and current probe	Quasi Peak / 9 kHz	97 – 87	53 – 43
	0,5 – 30			87	43
	0,15 – 0,5	CVP and current probe	Average / 9 kHz	84 – 74	40 – 30
	0,5 – 30			74	30
A10.3	0,15 – 0,5	Current Probe	Quasi Peak / 9 kHz	n/a	53 – 43
	0,5 – 30				43
	0,15 – 0,5	Current Probe	Average / 9 kHz		40 – 30
	0,5 – 30				30
NOTE 1 The choice of coupling device and measurement procedure is defined in Annex C.					
NOTE 2 AC mains power ports shall meet the limits given in Table A.8.					
NOTE 3 The test shall cover the entire frequency range.					
NOTE 4 The application of the voltage and/or current limits is dependent on the measurement procedure used. Refer to Table C.1 for applicability.					
NOTE 5 Testing is required at only one EUT supply voltage and frequency.					
NOTE 6 Applicable to ports listed above and intended to connect to cables longer than 3 m.					



Table A.11 – Requirements for asymmetric mode conducted emissions from Class B equipment

Applicable to					
1. wired network ports (3.1.30) 2. optical fibre ports (3.1.24) with metallic shield or tension members 3. broadcast receiver tuner ports (3.1.8) 4. antenna ports (3.1.3)					
Table clause	Frequency range MHz	Coupling device (see Table A.7)	Detector type / bandwidth	Class B voltage limits dB(μV)	Class B current limits dB(μA)
A11.1	0,15 – 0,5	AAN	Quasi Peak / 9 kHz	84 – 74	n/a
	0,5 – 30			74	
	0,15 – 0,5	AAN	Average / 9 kHz	74 – 64	
	0,5 – 30			64	
A11.2	0,15 – 0,5	CVP and current probe	Quasi Peak / 9 kHz	84 – 74	40 – 30
	0,5 – 30			74	30
	0,15 – 0,5	CVP and current probe	Average / 9 kHz	74 – 64	30 – 20
	0,5 – 30			64	20
A11.3	0,15 – 0,5	Current Probe	Quasi Peak / 9 kHz	n/a	40 – 30
	0,5 – 30				30
	0,15 – 0,5	Current Probe	Average / 9 kHz		30 – 20
	0,5 – 30				20
NOTE 1 The choice of coupling device and measurement procedure is defined in Annex C. NOTE 2 Screened ports including TV broadcast receiver tuner ports are tested with a common-mode impedance of 150 Ω. This is typically accomplished with the screen terminated by 150 Ω to earth. NOTE 3 AC mains power ports shall meet the limits given in Table A.9. NOTE 4 The test shall cover the entire frequency range. NOTE 5 The application of the voltage and/or current limits is dependent on the measurement procedure used. Refer to Table C.1 for applicability. NOTE 6 Testing is required at only one EUT supply voltage and frequency. NOTE 7 Applicable to ports listed above and intended to connect to cables longer than 3 m.					



4.4. Measurement Equipment


Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
Test Receiver	R&S	ESCI	100565	2016.03.26	2017.03.25
AMN	R&S	ESH2-Z5	100182	2016.08.31	2017.08.30
Two-Line V-Network	R&S	ENV216	100325	/	/
ISN	FCC	FCC-TLISN-T2-02	20379	2016.03.26	2017.03.25
ISN	FCC	FCC-TLISN-T4-02	20380	2016.03.26	2017.03.25
ISN	FCC	FCC-TLISN-T8-02	20381	2016.03.26	2017.03.25
ISN	TESEQ	ISN ST08	30175	2016.03.26	2017.03.25
Current Probe	R&S	EZ-17	100303	2016.03.26	2017.03.25
Passive Voltage Probe	R&S	ESH2-Z3	100026	2016.03.26	2017.03.25
Pulse Limiter	R&S	ESH3-Z2	100529	2016.03.26	2017.03.25
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-004	2016.03.29	2017.03.28
EZ-EMC	Fala	Ver CT3A1	N/A	N/A	N/A



4.5. Test Result and Data

4.5.1 Conducted Emission for Power Port Test Data

Test Mode :	Mode 1: Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(110V/60Hz)		
AC Power :	AC 110V/60Hz	Phase :	LINE
Equipment :	NETWORK VIDEO RECORDER	Model No :	DHI-NVR4232-4KS2
Temperature :	22°C	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/26




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1499	10.13	-9.45	0.68	66.00	-65.32	QP
2	0.1499	10.13	-12.44	-2.31	56.00	-58.31	AVG
3	0.1785	10.12	22.74	32.86	64.55	-31.69	QP
4	0.1785	10.12	9.58	19.70	54.55	-34.85	AVG
5	0.2180	10.12	19.69	29.81	62.89	-33.08	QP
6	0.2180	10.12	8.80	18.92	52.89	-33.97	AVG
7	0.2380	10.12	17.99	28.11	62.16	-34.05	QP
8	0.2380	10.12	7.97	18.09	52.16	-34.07	AVG
9	0.5620	10.16	20.37	30.53	56.00	-25.47	QP
10	0.5620	10.16	14.08	24.24	46.00	-21.76	AVG
11	12.9979	10.41	29.71	40.12	60.00	-19.88	QP
12	12.9979	10.41	24.39	34.80	50.00	-15.20	AVG

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 1: Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(110V/60Hz)		
AC Power :	AC 110V/60Hz	Phase :	NEUTRAL
Equipment :	NETWORK VIDEO RECORDER	Model No :	DHI-NVR4232-4KS2
Temperature :	22°C	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/26




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	10.13	27.68	37.81	65.99	-28.18	QP
2	0.1500	10.13	9.03	19.16	55.99	-36.83	AVG
3	0.1700	10.13	23.23	33.36	64.96	-31.60	QP
4	0.1700	10.13	4.56	14.69	54.96	-40.27	AVG
5	0.2020	10.13	21.51	31.64	63.52	-31.88	QP
6	0.2020	10.13	6.75	16.88	53.52	-36.64	AVG
7	0.5660	10.15	21.61	31.76	56.00	-24.24	QP
8	0.5660	10.15	15.16	25.31	46.00	-20.69	AVG
9	3.4820	10.21	12.74	22.95	56.00	-33.05	QP
10	3.4820	10.21	3.43	13.64	46.00	-32.36	AVG
11	12.9420	10.41	29.90	40.31	60.00	-19.69	QP
12	12.9420	10.41	24.78	35.19	50.00	-14.81	AVG

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 4: Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(230V/50Hz)		
AC Power :	AC 230V/50Hz	Phase :	LINE
Equipment :	NETWORK VIDEO RECORDER	Model No :	DHI-NVR4232-4KS2
Temperature :	22°C	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/26




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	10.13	25.21	35.34	65.99	-30.65	QP
2	0.1500	10.13	8.72	18.85	55.99	-37.14	AVG
3	0.1758	10.12	23.04	33.16	64.68	-31.52	QP
4	0.1758	10.12	9.69	19.81	54.68	-34.87	AVG
5	0.2180	10.12	18.23	28.35	62.89	-34.54	QP
6	0.2180	10.12	8.09	18.21	52.89	-34.68	AVG
7	0.2620	10.13	15.70	25.83	61.36	-35.53	QP
8	0.2620	10.13	7.31	17.44	51.36	-33.92	AVG
9	0.5620	10.16	20.44	30.60	56.00	-25.40	QP
10	0.5620	10.16	13.95	24.11	46.00	-21.89	AVG
11	12.8979	10.41	30.09	40.50	60.00	-19.50	QP
12	12.8979	10.41	24.96	35.37	50.00	-14.63	AVG

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 4: Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(230V/50Hz)		
AC Power :	AC 230V/50Hz	Phase :	NEUTRAL
Equipment :	NETWORK VIDEO RECORDER	Model No :	DHI-NVR4232-4KS2
Temperature :	22°C	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/26



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	10.13	26.69	36.82	65.99	-29.17	QP
2	0.1500	10.13	8.10	18.23	55.99	-37.76	AVG
3	0.1700	10.13	23.68	33.81	64.96	-31.15	QP
4	0.1700	10.13	5.12	15.25	54.96	-39.71	AVG
5	0.5660	10.15	21.72	31.87	56.00	-24.13	QP
6	0.5660	10.15	15.04	25.19	46.00	-20.81	AVG
7	2.9260	10.20	10.79	20.99	56.00	-35.01	QP
8	2.9260	10.20	3.96	14.16	46.00	-31.84	AVG
9	3.4820	10.21	12.36	22.57	56.00	-33.43	QP
10	3.4820	10.21	3.41	13.62	46.00	-32.38	AVG
11	12.9419	10.41	30.01	40.42	60.00	-19.58	QP
12	12.9419	10.41	24.91	35.32	50.00	-14.68	AVG

Note: Measurement Level = Reading Level + Correct Factor



4.5.2 Conducted Emission for Telecommunication Port Test Data

Test Mode :	Mode 1: Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(LAN 100M)(110V/60Hz)		
AC Power :	AC 110V/60Hz	Phase :	100Mbps
Equipment :	NETWORK VIDEO RECORDER	Model No :	DHI-NVR4232-4KS2
Temperature :	22°C	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/26



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.5580	19.59	46.42	66.01	74.00	-7.99	QP
2	0.5580	19.59	39.91	59.50	64.00	-4.50	AVG
3	0.8620	19.41	38.21	57.62	74.00	-16.38	QP
4	0.8620	19.41	31.10	50.51	64.00	-13.49	AVG
5	1.4620	19.25	36.37	55.62	74.00	-18.38	QP
6	1.4620	19.25	29.82	49.07	64.00	-14.93	AVG
7	2.7180	19.32	35.87	55.19	74.00	-18.81	QP
8	2.7180	19.32	29.89	49.21	64.00	-14.79	AVG
9	3.2740	19.41	33.29	52.70	74.00	-21.30	QP
10	3.2740	19.41	26.63	46.04	64.00	-17.96	AVG
11	25.5740	19.81	22.66	42.47	74.00	-31.53	QP
12	25.5740	19.81	17.34	37.15	64.00	-26.85	AVG

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 2: Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(LAN 100M)(230V/50Hz)		
AC Power :	AC 230V/50Hz	Phase :	100Mbps
Equipment :	NETWORK VIDEO RECORDER	Model No :	DHI-NVR4232-4KS2
Temperature :	22°C	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/26



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.3700	19.61	39.87	59.48	76.50	-17.02	QP
2	0.3700	19.61	33.21	52.82	66.50	-13.68	AVG
3	0.5580	19.59	46.42	66.01	74.00	-7.99	QP
4	0.5580	19.59	39.94	59.53	64.00	-4.47	AVG
5	0.8620	19.41	38.14	57.55	74.00	-16.45	QP
6	0.8620	19.41	30.92	50.33	64.00	-13.67	AVG
7	1.0020	19.30	38.21	57.51	74.00	-16.49	QP
8	1.0020	19.30	31.10	50.40	64.00	-13.60	AVG
9	1.5180	19.24	36.59	55.83	74.00	-18.17	QP
10	1.5180	19.24	29.85	49.09	64.00	-14.91	AVG
11	2.2220	19.24	36.37	55.61	74.00	-18.39	QP
12	2.2220	19.24	30.24	49.48	64.00	-14.52	AVG

Note: Measurement Level = Reading Level + Correct Factor

Test engineer: *Sun. Zhang*




4.6. Test Photographs of Power Port

Front View



Rear View






4.7. Test Photographs of Telecommunication Port

Front View



Rear View





5. Test of Radiated Emission

5.1. Test Limit

The EUT shall meet the limits of below Table when measured at the measuring distance R in accordance with the methods described in European Standard EN 55032. If the reading on the measuring receiver shows fluctuations close to the limit, the reading shall be observed for at least 15 s at each measurement frequency; the highest reading shall be recorded, with the exception of any brief isolated high reading, which shall be ignored.

Table 1 – Required highest frequency for radiated measurement

Highest internal frequency (F_x)	Highest measured frequency
$F_x \leq 108$ MHz	1 GHz
108 MHz $< F_x \leq 500$ MHz	2 GHz
500 MHz $< F_x \leq 1$ GHz	5 GHz
$F_x > 1$ GHz	$5 \times F_x$ up to a maximum of 6 GHz

NOTE 1 For FM and TV broadcast receivers, F_x is determined from the highest frequency generated or used excluding the local oscillator and tuned frequencies.

NOTE 2 F_x is defined in 3.1.19.

Where the F_x is unknown, the radiated emission measurements shall be performed up to 6 GHz.

Table A.2 – Requirements for radiated emissions at frequencies up to 1 GHz for Class A equipment

Table clause	Frequency range MHz	Measurement		Class A limits dB(μ V/m)
		Distance m	Detector type/ bandwidth	OATS/SAC (see Table A.1)
A2.1	30 – 230	10	Quasi Peak / 120 kHz	40
	230 – 1 000			47
A2.2	30 – 230	3		50
	230 – 1 000			57

NOTE Apply only A2.1 or A2.2 across the entire frequency range.

Table A.3 – Requirements for radiated emissions at frequencies above 1 GHz for Class A equipment

Table clause	Frequency range MHz	Measurement		Class A limits dB(μ V/m)
		Distance m	Detector type/ bandwidth	FSOATS (see Table A.1)
A3.1	1 000 – 3 000	3	Average / 1 MHz	56
	3 000 – 6 000			60
A3.2	1 000 – 3 000		Peak / 1 MHz	76
	3 000 – 6 000			80

NOTE Apply A3.1 and A3.2 across the frequency range from 1 000 MHz to the highest required frequency of measurement derived from Table 1.



Table A.4 – Requirements for radiated emissions at frequencies up to 1 GHz for Class B equipment

Table clause	Frequency range MHz	Measurement		Class B limits dB(μV/m)	
		Distance m	Detector type/ bandwidth	OATS/SAC (see Table A.1)	
A4.1	30 – 230	10	Quasi Peak / 120 kHz	30	
	230 – 1 000			37	
A4.2	30 – 230	3		40	
	230 – 1 000			47	

NOTE Apply only table clause A4.1 or A4.2 across the entire frequency range.

Table A.5 – Requirements for radiated emissions at frequencies above 1 GHz for Class B equipment

Table clause	Frequency range MHz	Measurement		Class B limits dB(μV/m)	
		Distance m	Detector type/ bandwidth	FSOATS (see Table A.1)	
A5.1	1 000 – 3 000	3	Average/ 1 MHz	50	
	3 000 – 6 000			54	
A5.2	1 000 – 3 000		Peak/ 1 MHz	70	
	3 000 – 6 000			74	

NOTE Apply A5.1 and A5.2 across the frequency range from 1 000 MHz to the highest required frequency of measurement derived from Table 1.

Table A.6 – Requirements for radiated emissions from FM receivers

Table clause	Frequency range MHz	Measurement		Class B limit dB(μV/m)		
		Distance m	Detector type/ bandwidth	Fundamental	Harmonics	
				OATS/SAC (see Table A.1)	OATS/SAC (see Table A.1)	
A6.1	30 – 230	10	Quasi peak/ 120 kHz	50	42	
	230 – 300				42	
	300 – 1 000				46	
A6.2	30 – 230	3		Quasi peak/ 120 kHz	60	52
	230 – 300					52
	300 – 1 000					56

NOTE 1 Apply only A.6.1 or A.6.2 across the entire frequency range.

NOTE 2 These relaxed limits apply only to emissions at the fundamental and harmonic frequencies of the local oscillator. Signals at all other frequencies shall be compliant with the limits given in Table A.4.



Table A.12 – Requirements for conducted differential voltage emissions from Class B equipment

Applicable to						
1. TV broadcast receiver tuner ports (3.1.8) with an accessible connector						
2. RF modulator output ports (3.1.27)						
3. FM broadcast receiver tuner ports (3.1.8) with an accessible connector						
Table clause	Frequency range MHz	Detector type/ bandwidth	Class B limits dB(μV) 75 Ω			Applicability
			Other	Local Oscillator Fundamental	Local Oscillator Harmonics	
A12.1	30 – 950	For frequencies ≤1 GHz	46	46	46	See NOTE 1
	950 – 2 150		46	54	54	
A12.2	950 – 2 150	Quasi Peak/ 120 kHz	46	54	54	See NOTE 2
A12.3	30 – 300		For frequencies ≥1 GHz	46	54	50
	300 – 1 000	52				
A12.4	30 – 300	Peak/ 1 MHz	46	66	59	See NOTE 4
	300 – 1 000				52	
A12.5	30 – 950	Peak/ 1 MHz	46	76	46	See NOTE 5
	950 – 2 150			n/a	54	

NOTE 1 Television receivers (analogue or digital), video recorders and PC TV broadcast receiver tuner cards working in channels between 30 MHz and 1 GHz, and digital audio receivers.

NOTE 2 Tuner units (not the LNB) for satellite signal reception.

NOTE 3 Frequency modulation audio receivers and PC tuner cards.

NOTE 4 Frequency modulation car radios.

NOTE 5 Applicable to EUTs with RF modulator output ports (for example DVD equipment, video recorders, camcorders and decoders etc.) designed to connect to TV broadcast receiver tuner ports.

NOTE 6 Testing is required at only one EUT supply voltage and frequency.

NOTE 7 The term 'other' refers to all emissions other than the fundamental and the harmonics of the local oscillator.

NOTE 8 The test shall be performed with the device operating at each reception channel.

NOTE 9 The test shall cover the entire frequency range.




5.4. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
EMI Test Receiver	R&S	ESCI7	100968	2016.03.26	2017.03.25
Preamplifier	Agilent	87405B	My39500554	2016.03.26	2017.03.25
Preamplifier	Agilent	8449B	3008A02342	2016.03.26	2017.03.25
Bilog Antenna	Sunol Science	JB1	A072414-1	2016.04.16	2017.04.15
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-618	2016.04.16	2017.04.15
Spectrum Analyzer	R&S	FSP40	100324	2016.03.26	2017.03.25
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-001	2016.03.29	2017.03.28
EZ-EMC	Fala	Ver CT3A1	N/A	N/A	N/A



5.5. Test Result and Data (30MHz ~ 1GHz)

Test Mode :	Mode 1: Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(110V/60Hz)		
AC Power :	AC 110V/60Hz	Ant. Polarization:	Horizontal
Equipment :	NETWORK VIDEO RECORDER	Model No :	DHI-NVR4232-4KS2
Temp :	23°C	Humidity :	52%
Pressure(mbar) :	1002	Date :	2016/11/26




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	30.0000	-3.26	28.31	25.05	30.00	-4.95	QP	400	18
2	140.5800	-10.43	34.78	24.35	30.00	-5.65	QP	400	63
3	191.9900	-10.54	32.39	21.85	30.00	-8.15	QP	400	0
4	282.1999	-8.82	30.42	21.60	37.00	-15.40	QP	100	0
5	449.0400	-4.58	29.74	25.16	37.00	-11.84	QP	400	29
6	934.0398	3.85	26.34	30.19	37.00	-6.81	QP	100	54

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 1: Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(110V/60Hz)		
AC Power :	AC 110V/60Hz	Ant. Polarization:	Vertical
Equipment :	NETWORK VIDEO RECORDER	Model No :	DHI-NVR4232-4KS2
Temp :	23°C	Humidity :	52%
Pressure(mbar) :	1002	Date :	2016/11/26




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	30.0000	-3.26	23.80	20.54	30.00	-9.46	QP	100	360
2	46.4900	-14.21	31.86	17.65	30.00	-12.35	QP	400	60
3	157.0699	-10.80	36.37	25.57	30.00	-4.43	QP	100	91
4	279.2900	-8.87	28.60	19.73	37.00	-17.27	QP	100	98
5	895.2400	3.40	24.87	28.27	37.00	-8.73	QP	100	62
6	933.0700	3.84	27.28	31.12	37.00	-5.88	QP	400	122

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 4: Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(230V/50Hz)		
AC Power :	AC 230V/50Hz	Ant. Polarization:	Horizontal
Equipment :	NETWORK VIDEO RECORDER	Model No :	DHI-NVR4232-4KS2
Temp :	23°C	Humidity :	52%
Pressure(mbar) :	1002	Date :	2016/11/26




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	32.9099	-5.36	28.53	23.17	30.00	-6.83	QP	100	8
2	125.0600	-9.77	32.19	22.42	30.00	-7.58	QP	400	94
3	191.9900	-10.54	32.39	21.85	30.00	-8.15	QP	400	215
4	445.1600	-4.67	28.89	24.22	37.00	-12.78	QP	400	0
5	554.7698	-1.96	26.56	24.60	37.00	-12.40	QP	100	0
6	971.8700	4.62	26.28	30.90	37.00	-6.10	QP	400	326

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 4: Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(230V/50Hz)		
AC Power :	AC 230V/50Hz	Ant. Polarization:	Vertical
Equipment :	NETWORK VIDEO RECORDER	Model No :	DHI-NVR4232-4KS2
Temp :	23°C	Humidity :	52%
Pressure(mbar) :	1002	Date :	2016/11/26




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	30.0000	-3.26	25.30	22.04	30.00	-7.96	QP	100	65
2	157.0699	-10.80	37.37	26.57	30.00	-3.43	QP	100	213
3	279.2900	-8.87	29.60	20.73	37.00	-16.27	QP	400	0
4	405.3899	-5.26	27.40	22.14	37.00	-14.86	QP	100	0
5	674.0800	-0.13	24.99	24.86	37.00	-12.14	QP	100	297
6	933.0700	3.84	29.28	33.12	37.00	-3.88	QP	400	48

Note: Measurement Level = Reading Level + Correct Factor



5.6. Test Result and Data (1GHz ~ 6GHz)

Test Mode :	Mode 1: Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(110V/60Hz)		
AC Power :	AC 110V/60Hz	Ant. Polarization:	Horizontal
Equipment :	NETWORK VIDEO RECORDER	Model No :	DHI-NVR4232-4KS2
Temp :	23°C	Humidity :	52%
Pressure(mbar) :	1002	Date :	2016/11/26




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	1103.000	-5.29	31.54	26.25	50.00	-23.75	AVG	200	360
2	1105.000	-5.28	50.29	45.01	70.00	-24.99	peak	200	360
3	1197.000	-4.66	28.79	24.13	50.00	-25.87	AVG	100	360
4	1200.000	-4.64	46.44	41.80	70.00	-28.20	peak	100	360
5	1500.000	-2.64	47.24	44.60	70.00	-25.40	peak	200	291
6	1502.000	-2.63	26.31	23.68	50.00	-26.32	AVG	200	291
7	2040.000	-1.00	42.17	41.17	70.00	-28.83	peak	200	84
8	2043.000	-0.98	24.08	23.10	50.00	-26.90	AVG	200	84
9	2442.000	1.05	25.96	27.01	50.00	-22.99	AVG	200	7
10	2445.000	1.07	43.34	44.41	70.00	-25.59	peak	200	7
11	3053.000	4.28	22.15	26.43	54.00	-27.57	AVG	200	0
12	3055.000	4.29	40.92	45.21	74.00	-28.79	peak	200	0

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 1: Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(110V/60Hz)		
AC Power :	AC 110V/60Hz	Ant. Polarization:	Vertical
Equipment :	NETWORK VIDEO RECORDER	Model No :	DHI-NVR4232-4KS2
Temp :	23°C	Humidity :	52%
Pressure(mbar) :	1002	Date :	2016/11/26




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	1083.000	-5.43	32.61	27.18	50.00	-22.82	AVG	100	242
2	1085.000	-5.41	52.51	47.10	70.00	-22.90	peak	100	242
3	1223.000	-4.49	28.97	24.48	50.00	-25.52	AVG	200	316
4	1225.000	-4.48	48.02	43.54	70.00	-26.46	peak	200	316
5	1500.000	-2.64	47.52	44.88	70.00	-25.12	peak	100	286
6	1501.000	-2.64	29.42	26.78	50.00	-23.22	AVG	100	286
7	2800.000	3.01	41.91	44.92	70.00	-25.08	peak	100	9
8	2802.000	3.02	22.14	25.16	50.00	-24.84	AVG	100	9
9	3090.000	4.40	41.11	45.51	74.00	-28.49	peak	200	51
10	3093.000	4.41	22.30	26.71	54.00	-27.29	AVG	200	51
11	4360.000	9.33	38.59	47.92	74.00	-26.08	peak	100	0
12	4362.000	9.34	20.58	29.92	54.00	-24.08	AVG	100	0

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 4: Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(230V/50Hz)		
AC Power :	AC 230V/50Hz	Ant. Polarization:	Horizontal
Equipment :	NETWORK VIDEO RECORDER	Model No :	DHI-NVR4232-4KS2
Temp :	23°C	Humidity :	52%
Pressure(mbar) :	1002	Date :	2016/11/26




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	1078.000	-5.46	28.64	23.18	50.00	-26.82	AVG	200	215
2	1080.000	-5.45	47.94	42.49	70.00	-27.51	peak	200	360
3	1223.000	-4.49	29.12	24.63	50.00	-25.37	AVG	100	360
4	1225.000	-4.48	48.10	43.62	70.00	-26.38	peak	100	215
5	1500.000	-2.64	49.15	46.51	70.00	-23.49	peak	200	360
6	1501.000	-2.64	30.34	27.70	50.00	-22.30	AVG	200	360
7	1575.000	-2.42	43.88	41.46	70.00	-28.54	peak	200	29
8	1576.000	-2.42	24.78	22.36	50.00	-27.64	AVG	200	29
9	2448.000	1.08	22.06	23.14	50.00	-26.86	AVG	100	84
10	2450.000	1.10	41.06	42.16	70.00	-27.84	peak	100	84
11	3098.000	4.42	21.39	25.81	54.00	-28.19	AVG	100	0
12	3100.000	4.43	40.76	45.19	74.00	-28.81	peak	100	215

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 4: Full System(VGA Mode:1920*1080@60Hz + HDMI Mode:1920*1080@60Hz)(230V/50Hz)		
AC Power :	AC 230V/50Hz	Ant. Polarization:	Vertical
Equipment :	NETWORK VIDEO RECORDER	Model No :	DHI-NVR4232-4KS2
Temp :	23°C	Humidity :	52%
Pressure(mbar) :	1002	Date :	2016/11/26



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	1084.000	-5.42	32.15	26.73	50.00	-23.27	AVG	100	152
2	1085.000	-5.41	53.74	48.33	70.00	-21.67	peak	100	152
3	1259.000	-4.25	30.47	26.22	50.00	-23.78	AVG	200	0
4	1260.000	-4.24	49.45	45.21	70.00	-24.79	peak	200	0
5	1500.000	-2.64	50.68	48.04	70.00	-21.96	peak	100	0
6	1501.000	-2.64	31.69	29.05	50.00	-20.95	AVG	100	0
7	2160.000	-0.38	41.55	41.17	70.00	-28.83	peak	100	326
8	2162.000	-0.37	22.53	22.16	50.00	-27.84	AVG	100	326
9	2450.000	1.10	42.41	43.51	70.00	-26.49	peak	200	21
10	2453.000	1.11	23.59	24.70	50.00	-25.30	AVG	200	21
11	2998.000	4.11	21.05	25.16	50.00	-24.84	AVG	100	0
12	3000.000	4.12	40.35	44.47	70.00	-25.53	peak	100	0


Note: Measurement Level = Reading Level + Correct Factor

Test engineer: Sun. Zhang




5.7. Test Photographs (30MHz~1GHz)

Front View



Rear View






5.8. Test Photographs (1GHz~6GHz)

Front View



Rear View





6. Harmonics Test

6.1. Limits of Harmonics Current Measurement

Limits for Class A equipment

Harmonics Order n	Max. permissible harmonics current A	Harmonics Order n	Max. permissible harmonics current A
Odd harmonics		Even harmonics	
3	2.30	2	1.08
5	1.14	4	0.43
7	0.77	6	0.30
9	0.40	8<=n<=40	0.23x8/n
11	0.33		
13	0.21		
15<=n<=39	0.15x15/n		

(b) Limits for Class B equipment

For Class B equipment, the harmonics of the input current shall not exceed the values given in Table that is the limit of Class A multiplied by a factor of 1,5.

(c) Limits for Class C equipment

Harmonics Order n	Maximum permissible harmonic current expressed as a percentage of the input current at the fundamental frequency %
2	2
3	$30 \cdot \lambda^*$
5	10
7	7
9	5
11<n<39 (odd harmonics only)	3

* λ is the circuit power factor

(d) Limits for Class D equipment

Harmonics Order n	Maximum permissible harmonic current per watt mA/W	Maximum permissible harmonic current A
3	3.4	2.30
5	1.9	1.14
7	1.0	0.77
9	0.5	0.40
11	0.35	0.33
11 < n < 39 (odd harmonics only)	3.85/n	See limit of Class A

NOTE: According to section 7 of EN 61000-3-2, the above limits for all equipment except for lighting equipment having an active input power > 75 W and no limits apply for equipment with an active input power up to and including 75 W.




6.2. Measurement equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
EMC Emission Tester	EMCPARTNER	Harmonics-1000	159	2016.03.26	2017.03.25
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-004	2016.03.29	2017.03.28
HARCS	EMC Partner AG	Ver 4.18	N/A	N/A	N/A



6.3. Test Result and Data

Basic Standard	:	EN 61000-3-2
Final Test Result	:	PASS
Test Mode	:	Mode 1
Equipment	:	NETWORK VIDEO RECORDER
Model No.	:	DHI-NVR4232-4KS2
Temperature	:	21°C
Humidity	:	52 %
Atmospheric Pressure	:	100 kPa
Test Date	:	Nov 26, 2016



Harmonic Emission - IEC 61000-3-2 , EN 61000-3-2 , (EN60555-2)

2016-11-26 10:24:48

Urms = 230.3 V P = 6.111 W THC = 0.057 A
 Irms = 0.070 A pf = 0.380

Range: 1 A
 V-nom: 230 V
 TestTime: 15 min (100%)

Test completed, Result: PASSED

HAR-1000 EMC-Partner

Full Bar : Actual Values
 Empty Bar : Maximum Values
 Blue : Current , Green : Voltage , Red : Failed

Urms = 230.3V Freq = 49.987 Range: 1 A
 Irms = 0.070A Ipk = 0.285A cf = 4.077
 P = 6.111W S = 16.08VA pf = 0.380
 THDi = 133 % THDu = 1.60 % Class A
 Test - Time : 15min (100 %)
 Test completed, Result: PASSED



Order	Freq. [Hz]	I _{rms} [A]	I _{rms} %L [%]	I _{max} [A]	I _{max} %L [%]	Limit [A]
1	50	0.0430		0.0541		
2	100	0.0007	0.0622	0.0013	0.1187	1.0800
3	150	0.0262	1.1384	0.0328	1.4250	2.3000
4	200	0.0011	0.2555	0.0015	0.3407	0.4300
5	250	0.0244	2.1362	0.0306	2.6823	1.1400
6	300	0.0015	0.4883	0.0019	0.6307	0.3000
7	350	0.0231	3.0042	0.0290	3.7652	0.7700
8	400	0.0014	0.6104	0.0018	0.7961	0.2300
9	450	0.0215	5.3864	0.0271	6.7749	0.4000
10	500	0.0017	0.9288	0.0021	1.1610	0.1840
11	550	0.0176	5.3452	0.0221	6.6954	0.3300
12	600	0.0020	1.2738	0.0025	1.6320	0.1533
13	650	0.0149	7.0917	0.0187	8.9228	0.2100
14	700	0.0016	1.2539	0.0021	1.5790	0.1314
15	750	0.0126	8.3822	0.0158	10.539	0.1500
16	800	0.0015	1.3269	0.0020	1.6984	0.1150
17	850	0.0101	7.6090	0.0128	9.6381	0.1324
18	900	0.0015	1.4330	0.0018	1.7912	0.1022
19	950	0.0081	6.8034	0.0101	8.5042	0.1184
20	1000	0.0012	1.3269	0.0016	1.7249	0.0920
21	1050	0.0063	5.9245	0.0081	7.5195	0.1071
22	1100	0.0009	1.0947	0.0013	1.5325	0.0836
23	1150	0.0049	5.0537	0.0062	6.3639	0.0978
24	1200	0.0010	1.2738	0.0013	1.6718	0.0767
25	1250	0.0041	4.5437	0.0051	5.6966	0.0900
26	1300	0.0010	1.4662	0.0013	1.8974	0.0708
27	1350	0.0036	4.3213	0.0045	5.3467	0.0833
28	1400	0.0010	1.5790	0.0013	2.0434	0.0657
29	1450	0.0034	4.4054	0.0042	5.4281	0.0776
30	1500	0.0010	1.6917	0.0013	2.0898	0.0613
31	1550	0.0031	4.2887	0.0039	5.3819	0.0726
32	1600	0.0010	1.8045	0.0013	2.3353	0.0575
33	1650	0.0027	3.9388	0.0034	5.0130	0.0682
34	1700	0.0010	1.9173	0.0013	2.3684	0.0541
35	1750	0.0023	3.5129	0.0029	4.4623	0.0643
36	1800	0.0009	1.7912	0.0012	2.2689	0.0511
37	1850	0.0017	2.8103	0.0022	3.6133	0.0608
38	1900	0.0007	1.5126	0.0010	2.0168	0.0484
39	1950	0.0012	2.1159	0.0016	2.7507	0.0577
40	2000	0.0005	1.0615	0.0007	1.4595	0.0460


EUT is PASSED if:

- all Average values of the Individual Harmonic Currents (I_{avg}) are below 100% of the Individual Limits.
- all Maximum values of the Individual Harmonic Currents (I_{max}) are below 150% of the Individual Limits.

Test engineer: Sun Zhang



6.4. Test Photographs





7. Voltage Fluctuations Test

7.1. Test Procedure

The equipment shall be tested under the conditions of **Clause 5**.

The total impedance of the test circuit, excluding the appliance under test, but including the internal impedance of the supply source, shall be equal to the reference impedance.

The stability and tolerance of the reference impedance shall be adequate to ensure that the overall accuracy of $\pm 8\%$ is achieved during the whole assessment procedure.

7.2. Measurement Equipment


Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
EMC Emission Tester	EMCPARTNER	Harmonics-1000	159	2016.03.26	2017.03.25
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-004	2016.03.29	2017.03.28
HARCS	EMC Partner AG	Ver 4.18	N/A	N/A	N/A



7.3. Test Result and Data

Basic Standard	:	EN 61000-3-3
Final Test Result	:	PASS
Test Mode	:	Mode 1
Equipment	:	NETWORK VIDEO RECORDER
Model No.	:	DHI-NVR4232-4KS2
Temperature	:	21°C
Humidity	:	52 %
Atmospheric Pressure	:	100 kPa
Test Date	:	Nov 26, 2016

Flicker Emission IEC 61000-4-15 for 230V/50Hz



Actual Flicker (Fli): 0.01
Short-term Flicker (Pst): 0.08
 Limit (Pst): 1.00
Long-term Flicker (Plt): 0.08
 Limit (Plt): 0.65
Maximum Relative Volt. Change (dmax): 0.00%
 Limit (dmax): 4.00%
Relative Steady-state Voltage Change (dc): 0.13%
 Limit (dc): 3.30%
Tmax 3.30% (dt): 0.00ms
 Limit (dt>Lim): 500ms

Flicker Emission - IEC 61000-3-3 , EN 61000-3-3

Urms = 230.3 V P = 6.185 W
 Irms = 0.070 A pf = 0.382

2016-11-26 10:36:48

Range: 0.5 A
 V-nom: 230 V
 TestTime: 10 min (100%)

Test completed, Result: PASSED

HAR-1000 EMC-Partner

- Full Bar : Actual Values
- Empty Bar : Maximum Values
- Circles : Average Values
- Blue : Current , Green : Voltage , Red : Failed



Urms = 230.3V Freq = 50.013 Range: 0.5 A
Irms = 0.070A Ipk = 0.287A cf = 4.076
P = 6.185W S = 16.19VA pf = 0.382

Test - Time : 1 x 10min = 10min (100 %)

LIN (Line Impedance Network) : No LIN

Limits : Plt : 0.65 Pst : 1.00
dmax : 4.00 % dc : 3.30 %
dtLim: 3.30 % dt>Lim: 500ms

Test completed, Result: PASSED

Test engineer: Sun. Zhang



7.4. Test Photographs






8. Electrostatic Discharge Immunity Test

8.1. Test Procedure

- a. In the case of air discharge testing the climatic conditions shall be within the following ranges:
 - ambient temperature: 15°C to 35°C;
 - relative humidity : 30% to 60%;
 - atmospheric pressure : 86 KPa (860 mbar) to 106 KPa (1060 mbar).
- b. Test programs and software shall be chosen so as to exercise all normal modes of operation of the EUT. The use of special exercising software is encouraged, but permitted only where it can be shown that the EUT is being comprehensively exercised.
- c. The test voltage shall be increased from the minimum to the selected test severity level, in order to determine any threshold of failure. The final severity level should not exceed the product specification value in order to avoid damage to the equipment.
- d. The test shall be performed with both air discharge and contact discharge. On reselected points at least 10 single discharges (in the most sensitive polarity) shall be applied on air discharge. On reselected points at least 25 single discharges (in the most sensitive polarity) shall be applied on contact discharge.
- e. For the time interval between successive single discharges an initial value of one second is recommended. Longer intervals may be necessary to determine whether a system failure has occurred.
- f. In the case of contact discharges, the tip of the discharge electrode shall touch the EUT before the discharge switch is operated.
- g. In the case of painted surface covering a conducting substrate, the following procedure shall be adopted :
 - If the coating is not declared to be an insulating coating by the equipment manufacturer, then the pointed tip of the generator shall penetrate the coating so as to make contact with the conducting substrate.
 - Coating declared as insulating by the manufacturer shall only be submitted to the air discharge.
 - The contact discharge test shall not be applied to such surfaces.
- h. In the case of air discharges, the round discharge tip of the discharge electrode shall be approached as fast as possible (without causing mechanical damage) to touch the EUT . After each discharge, the ESD generator (discharge electrode) shall be removed from the EUT. The generator is then retriggered for a new single discharge. This procedure shall be repeated until the discharges are completed. In the case of an air discharge test, the discharge switch, which is used for contact discharge, shall be closed.

8.2. Test Setup for Tests Performed in Laboratory



The test setup consists of the test generator, EUT and auxiliary instrumentation necessary to perform DIRECT and INDIRECT application of discharges to the EUT as applicable, in the following manner :

- a. Contact Discharge to the conductive surfaces and to coupling plane;
- b. Air Discharge at insulating surfaces.

The preferred test method is that of type tests performed in laboratories and the only accepted method of demonstrating conformance with this standard. The EUT was arranged as closely as possible to arrangement in final installed conditions.

A ground reference plane was provided on the floor of the test site. It was a metallic sheet (copper or aluminum) of 0.25 mm, minimum thickness; other metallic may be used but they shall have at least 0.65 mm thickness. In the CerpPASS Technology Corp., we provided 1 mm thickness stainless steel ground reference plane. The minimum size of the ground reference plane is 2.5 m x 2.5 m, the exact size depending on the dimensions of the EUT. It was connected to the protective grounding system.

The EUT was arranged and connected according to its functional requirements. A distance of 1m minimum was provided between the EUT and the wall of the lab. and any other metallic structure. In cases where this length exceeds the length necessary to apply the discharges to the selected points, the excess length shall, where possible, be placed non-inductively off the ground reference plane and shall not come closer than 0.2m to other conductive parts in the test setup.

Where the EUT is installed on a metal table, the table was connected to the reference plane via a cable with a 470k ohm resistor located at each end, to prevent a build-up of charge. The test setup was consist a wooden table, 0.8m high, standing on the ground reference plane. A HCP, 1.6 m x 0.8 m, was placed on the table. The EUT and cables was isolated from the HCP by an insulating support 0.5 mm thick. The VCP size, 0.5 m x 0.5 m.



8.3. Test Severity Levels

Contact Discharge		Air Discharge	
Level	Test Voltage (KV) of Contact discharge	Level	Test Voltage (KV) of Air Discharge
1	±2	1	±2
2	±4	2	±4
3	±6	3	±8
4	±8	4	±15
X	Specified	X	Specified

Remark: "X" is an open level.

8.4. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
ESD Simulator	EM Test	dito	V0714102399	2016.04.21	2017.04.20
Tonometer	shanghaifengyun	DYM3	3251	2015.12.21	2016.12.20
Dehumidifier	ZEDO	ZD-220LB	CEP-TH-01	N/A	N/A
Humidifier	YADU	YZ-DS251C	CEP-TH-02	N/A	N/A
Temperature/ Humidity Meter	feiyang	N/A	102	2016.03.29	2017.03.28



8.5. Test Result and Data

Basic Standard : IEC 61000-4-2
 Product Standard : EN 50130-4: 2011
 Product Standard : EN 55024 : 2010
 Equipment : NETWORK VIDEO RECORDER
 Model No. : DHI-NVR4232-4KS2
 Final Test Result : PASS
 Temperature : 20°C
 Relative Humidity : 48%
 Atmospheric Pressure : 100 kPa
 Test Date : Nov 06, 2016

Mode 1

For EN 55024: 2010

Test Voltage: AC 230V/50Hz																
	Contact Discharge								Air Discharge							
	25 times / each								10 times / each							
Voltage	2 kV		4 kV		6 kV		8 kV		2 kV		4 kV		8 kV		10 kV	
Point\Polarity	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-
HCP	A	A	A	A	---	---	---	---	---	---	---	---	---	---	---	---
VCP	A	A	A	A	---	---	---	---	---	---	---	---	---	---	---	---
1-21	---	---	---	---	---	---	---	---	A	A	A	A	A	A	---	---
22-52	A	A	A	A	---	---	---	---	---	---	---	---	---	---	---	---

For EN 50130-4: 2011

Test Voltage: AC 230V/50Hz																
	Contact Discharge								Air Discharge							
	25 times / each								10 times / each							
Voltage	2 kV		4 kV		6 kV		8 kV		2 kV		4 kV		8 kV		10 kV	
Point\Polarity	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-
HCP	A	A	A	A	A	A	---	---	---	---	---	---	---	---	---	---
VCP	A	A	A	A	A	A	---	---	---	---	---	---	---	---	---	---
1-21	---	---	---	---	---	---	---	---	A	A	A	A	A	A	---	---
22-52	A	A	A	A	A	A	---	---	---	---	---	---	---	---	---	---



Test Voltage: AC 195.5V/50Hz																
	Contact Discharge								Air Discharge							
	25 times / each								10 times / each							
Voltage	2 kV		4 kV		6 kV		8 kV		2 kV		4 kV		8 kV		10 kV	
Point\Polarity	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-
HCP	A	A	A	A	A	A	---	---	---	---	---	---	---	---	---	---
VCP	A	A	A	A	A	A	---	---	---	---	---	---	---	---	---	---
1-21	---	---	---	---	---	---	---	---	A	A	A	A	A	A	---	---
22-52	A	A	A	A	A	A	---	---	---	---	---	---	---	---	---	---


Test Voltage: AC 253V/50Hz																
	Contact Discharge								Air Discharge							
	25 times / each								10 times / each							
Voltage	2 kV		4 kV		6 kV		8 kV		2 kV		4 kV		8 kV		10 kV	
Point\Polarity	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-
HCP	A	A	A	A	A	A	---	---	---	---	---	---	---	---	---	---
VCP	A	A	A	A	A	A	---	---	---	---	---	---	---	---	---	---
1-21	---	---	---	---	---	---	---	---	A	A	A	A	A	A	---	---
22-52	A	A	A	A	A	A	---	---	---	---	---	---	---	---	---	---



Test engineer Sun. Zhang





8.6. Test Photographs











9. Radio Frequency electromagnetic field immunity test


9.1. Test Procedure

- a. The equipment to be tested is placed in the center of the enclosure on a wooden table. The equipment is then connected to power and signal leads according to pertinent installation instructions.
- b. The antenna which is enabling the complete frequency range of 80-1000 MHz is placed 3m away from the equipment. The required field strength is determined by placing the field strength meter(s) on top of or directly alongside the equipment under test and monitoring the field strength meter via a remote field strength indicator outside the enclosure while adjusting the continuous-wave to the applicable antennae.
- c. The test is normally performed with the antenna facing the most sensitive side of the EUT. The polarization of the field generated by the bucolical antenna necessitates testing each position twice, once with the antenna positioned vertically and again with the antenna positioned horizontally. The circular polarization of the field from the log-spiral antenna makes a change of position of the antenna unnecessary.
- d. At each of the above conditions, the frequency range is swept 80-1000 MHz, pausing to adjust the R.F. signal level or to switch oscillators and antenna. The rate of sweep is in the order of 1.5×10^{-3} decades/s. The sensitive frequencies or frequencies of dominant interest may be discretely analyzed.

9.2. Test Severity Levels

Frequency Band : 80-1000 MHz	
Level	Test field strength (V/m)
1	1
2	3
3	10
X	Specified
Remark: "X" is an open class.	

9.3. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

NOTE:

TABLETOP EQUIPMENT

The EUT installed in a representative system as described in section 7 of IEC 61000-4-3 was placed on a non-conductive table 0.8 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.

FLOOR STANDING EQUIPMENT

The EUT installed in a representative system as described in section 7 of IEC 61000-4-3 was placed on a non-conductive wood support 0.1 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.



9.4. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
Signal Generator	R&S	SML03	103287	2016.03.26	2017.03.25
Power Sensor	R&S	NR P-Z91	100383	2016.03.26	2017.03.25
Power Sensor	R&S	NRP-Z91	100384	2016.03.26	2017.03.25
Power Meter	R&S	NRP	101206	2016.03.26	2017.03.25
Power Amplifier	BONN	BLWA0830-16 0/100/40D	076659	2016.03.26	2017.03.25
Istropic Electric Field Probe	EST.LINDGRE N	HI-6105	137445	2016.11.20	2017.11.19
EMS Antenna	R&S	HL046E	100028	N/A	N/A
Temperature/ Humidity Meter	feiyang	N/A	101	2016.03.29	2017.03.28
EMC-32	Rohde&Schwa rz	Ver 6.10.0	N/A	N/A	N/A



9.5. Test Result and Data

Basic Standard : IEC 61000-4-3
 Product Standard : EN 50130-4: 2011
 Product Standard : EN 55024 : 2010
 Equipment : NETWORK VIDEO RECORDER
 Model No. : DHI-NVR4232-4KS2
 Final Test Result : PASS
 Temperature : 21 °C
 Relative Humidity : 54%
 Atmospheric Pressure : 100 kPa
 Test Date : Nov 06, 2016

Mode 1

For EN 55024: 2010

Modulation : AM 80% , 1KHz sine wave , Dwell time: 3.0 S				
Frequency Step Size : 1 % of preceding frequency value				
Frequency (MHz)	Antenna Polarization	face	Field strength (V/m)	Result
80~1000	Horizontal &Vertical	Front	3 V/m	A
80~1000	Horizontal &Vertical	Rear	3 V/m	A
80~1000	Horizontal &Vertical	Left	3 V/m	A
80~1000	Horizontal &Vertical	Right	3 V/m	A

For EN 50130-4: 2011

Test Voltage: AC 230V/50Hz

Modulation : AM 80% , 1KHz sine wave , Dwell time: 3.0S				
Frequency Step Size : 1 % of preceding frequency value				
Frequency (MHz)	Antenna Polarization	face	Field strength (V/m)	Result
80~2700	Horizontal &Vertical	Front	10 V/m	A
80~2700	Horizontal &Vertical	Rear	10 V/m	A
80~2700	Horizontal &Vertical	Left	10 V/m	A
80~2700	Horizontal &Vertical	Right	10 V/m	A



Test Voltage: AC 195.5V/50Hz

Modulation : AM 80% , 1KHz sine wave , Dwell time: 3.0 S				
Frequency Step Size : 1 % of preceding frequency value				
Frequency (MHz)	Antenna Polarization	face	Field strength (V/m)	Result
80~2700	Horizontal &Vertical	Front	10 V/m	A
80~2700	Horizontal &Vertical	Rear	10 V/m	A
80~2700	Horizontal &Vertical	Left	10 V/m	A
80~2700	Horizontal &Vertical	Right	10 V/m	A


Test Voltage: AC 253V/50Hz

Modulation : AM 80% , 1KHz sine wave , Dwell time: 3.0 S				
Frequency Step Size : 1 % of preceding frequency value				
Frequency (MHz)	Antenna Polarization	face	Field strength (V/m)	Result
80~2700	Horizontal &Vertical	Front	10 V/m	A
80~2700	Horizontal &Vertical	Rear	10 V/m	A
80~2700	Horizontal &Vertical	Left	10 V/m	A
80~2700	Horizontal &Vertical	Right	10 V/m	A

Test engineer: Sun. Zhang



9.6. Test Photographs





10. Electrical Fast Transient/ Burst Immunity Test

10.1. Test Procedure

- a. In order to minimize the effect of environmental parameters on test results, the climatic conditions when test is carrying out shall comply with the following requirements:
 - ambient temperature: 15°C to 35°C;
 - relative humidity : 45% to 75%;
 - Atmospheric pressure: 86 Kpa (860 mbar) to 106 Kpa (1060 mbar).
- b. In order to minimize the effect of environmental parameters on test results, the electromagnetic environment of the laboratory shall not influence the test results.
- c. The variety and diversity of equipment and systems to be tested make it difficult to establish general criteria for the evaluation of the effects of fast transients/bursts on equipment and systems.
- d. Test on Power Line:
 - The EFT/B-generator was located on the GRP.
For floor standing equipment 1,0 m
For table top equipment 0,5 m
 - The EFT/B-generator provides the ability to apply the test voltage in a non-symmetrical condition to the power supply input terminals of the EUT.
- e. Test on Communication Lines
 - The coupling clamp is composed of a clamp unit for housing the cable (length more than 3 m), and was placed on the GRP.
 - The coupling clamp provides the ability of coupling the fast transient/bursts to the cable under test.
- f. The test results may be classified on the basic of the operating conditions and the functional specification of the equipment under test, according to the following performance criteria :
 - Normal performance within the specification limits.
 - Temporary degradation or loss of function or performance which is self-recoverable.
 - Temporary degradation or loss of function or performance which requires operator intervention or system reset.
 - Degradation or loss of function which is not recoverable due to damage of equipment (components).


10.2. Test Severity Levels

The following test severity levels are recommended for the fast transient/burst test :

Open circuit output test voltage $\pm 10\%$		
Level	On Power Supply	On I/O signal, data and control line
1	0.5 KV	0.25 KV
2	1.0 KV	0.50 KV
3	2.0 KV	1.00 KV
4	4.0 KV	2.00 KV
X	Specified	Specified

Remark : “ X ” is an open level. The level is subject to negotiation between the user and manufacturer or is specified by the manufacturer.

10.3. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

NOTE:

TABLETOP EQUIPMENT

The configuration consisted of a wooden table (0.1m high) standing on the Ground Reference Plane. The GRP consisted of a sheet of aluminum (at least 0.25mm thick and 2.5m square) connected to the protective grounding system. A minimum distance of 0.5m was provided between the EUT and the walls of the laboratory or any other metallic structure.

FLOOR STANDING EQUIPMENT

The EUT installed in a representative system as described in section 7 of IEC 61000-4-4 and its cables, were isolated from the Ground Reference Plane by an insulating support that is 0.1-meter thick. The GRP consisted of a sheet of aluminum (at least 0.25mm thick and 2.5m square) connected to the protective grounding system.



10.4. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
TRANSIENT	EMCPARTNER	TRA2000IN6	901	2016.03.26	2017.03.25
CDN	EMCPARTNER	CDN2000-06-32	121	2016.03.26	2017.03.25
Coupling clamp	EMCPARTNER	CN-EFT1000	547	2016.03.26	2017.03.25
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-005	2016.03.29	2017.03.28



10.5. Test Result and Data

Basic Standard : IEC 61000-4-4
 Product Standard : EN 50130-4: 2011
 Product Standard : EN 55024 : 2010
 Equipment : NETWORK VIDEO RECORDER
 Model No. : DHI-NVR4232-4KS2
 Final Test Result : PASS
 Temperature : 23 °C
 Relative Humidity : 52%
 Atmospheric Pressure : 100 kPa
 Test Date : Nov 06, 2016

Test Mode 1:

For EN 55024: 2010

Test Voltage: AC 230V/50Hz

Pulse : 5/50 ns		Repetition Rate: <u>5 kHz</u>			
Burst : 15m/300ms					
Test time : 1 min/each condition					
Voltage/ Mode/ Polarity/ Result/ Phase		<u>0.5 kV</u>		<u>1.0 kV</u>	
		+	-	+	-
Power Line	L	---	---	A	A
	N	---	---	A	A
	L-N	---	---	A	A
	PE	---	---	A	A
	L-PE	---	---	A	A
	N-PE	---	---	A	A
	L-N-PE	---	---	A	A
Signal Line	LAN Port	A	A	---	---
	POE Port	A	A	---	---



For EN 50130-4: 2011

Test Voltage: AC 230V/50Hz

Pulse : 5/50 ns		Repetition Rate: 5/100 kHz			
Burst : 15m/300ms					
Test time : 1 min/each condition					
Voltage/ Mode/ Polarity/ Result/ Phase		<u>1 kV</u>		<u>2.0 kV</u>	
		+	-	+	-
Power Line	L	---	---	A	A
	N	---	---	A	A
	L-N	---	---	A	A
	PE	---	---	A	A
	L-PE	---	---	A	A
	N-PE	---	---	A	A
	L-N-PE	---	---	A	A
Signal Line	LAN Port	A	A	---	---
	POE Port	A	A	---	---

Test Voltage: AC 195.5V/50Hz

Pulse : 5/50 ns		Repetition Rate: 5/100 kHz			
Burst : 15m/300ms					
Test time : 1 min/each condition					
Voltage/ Mode/ Polarity/ Result/ Phase		<u>1 kV</u>		<u>2.0 kV</u>	
		+	-	+	-
Power Line	L	---	---	A	A
	N	---	---	A	A
	L-N	---	---	A	A
	PE	---	---	A	A
	L-PE	---	---	A	A
	N-PE	---	---	A	A
	L-N-PE	---	---	A	A
Signal Line	LAN Port	A	A	---	---
	POE Port	A	A	---	---



Test Voltage: AC 253V/50Hz

Pulse : 5/50 ns		Repetition Rate: 5/100 kHz			
Burst : 15m/300ms					
Test time : 1 min/each condition					
Voltage/ Mode/ Polarity/ Result/ Phase		<u>1 kV</u>		<u>2.0 kV</u>	
		+	-	+	-
Power Line	L	---	---	A	A
	N	---	---	A	A
	L-N	---	---	A	A
	PE	---	---	A	A
	L-PE	---	---	A	A
	N-PE	---	---	A	A
	L-N-PE	---	---	A	A
Signal Line	LAN Port	A	A	---	---
	POE Port	A	A	---	---

Test engineer: Sun. Zhang



10.6. Test Photographs





11. Surge Immunity Test

11.1. Test Procedure


- a. Climatic conditions
The climatic conditions shall comply with the following requirements :
 - ambient temperature : 15 °C to 35 °C
 - relative humidity : 10 % to 75 %
 - atmospheric pressure : 86 kPa to 106 kPa (860 mbar to 1060 mbar)
- b. Electromagnetic conditions
the electromagnetic environment of the laboratory shall not influence the test results.
- c. The test shall be performed according the test plan that shall specify the test set-up with
 - generator and other equipment utilized;
 - test level (voltage/current);
 - generator source impedance;
 - internal or external generator trigger;
 - number of tests : at least five positive and five negative at the selected points;
 - repetition rate : maximum 1/min.
 - inputs and outputs to be tested;
 - representative operating conditions of the EUT;
 - sequence of application of the surge to the circuit;
 - phase angle in the case of AC. power supply;
 - actual installation conditions, for example :
 - AC : neutral earthed,
 - DC : (+) or (-) earthed to simulated the actual earthing conditions.
- d. If not otherwise specified the surges have to be applied synchronized to the voltage phase at the zero-crossing and the peak value of the AC. voltage wave (positive and negative).
- e. The surges have to be applied line to line and line(s) and earth. When testing line to earth, the test voltage has to be applied successively between each of the lines and earth, if there is no other specification.
- f. The test procedure shall also consider the non-linear current-voltage characteristics of the equipment under test. Therefore the test voltage has to be increased by steps up to the test level specified in the product standard or test plan.
- g. All lower levels including the selected test level shall be satisfied. For testing the secondary protection, the output voltage of the generator shall be increased up to the worst-case voltage breakdown level (let-through level) of the primary protection.
- h. If the actual operating signal sources are not available, that may be simulated. Under no circumstances may the test level exceed the product specification. The test shall be carried out according to a test plan.
- i. To find all critical points of the duty cycle of the equipment, a sufficient number of positive and negative test pulses shall be applied. For acceptance test previously unstressed equipment shall be used to the protection devices shall be replaced.

11.2. Test Severity Level

Level	Open-circuit test voltage, ± 10%, KV
1	0.5
2	1.0
3	2.0
4	4.0
X	Specified
NOTE: "X" is an open class. This level can be specified in the product specification.	



11.3. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

11.4. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
TRANSIENT	EMCPARTNER	TRA2000IN6	901	2016.03.26	2017.03.25
CDN	EMCPARTNER	CDN-UTP8	021	2016.03.26	2017.03.25
CDN	EMCPARTNER	CDN2000-06-32	121	2016.03.26	2017.03.25
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-005	2016.03.29	2017.03.28



11.5. Test Result and Data

Basic Standard : IEC 61000-4-5
 Product Standard : EN 50130-4: 2011
 Product Standard : EN 55024 : 2010
 Equipment : NETWORK VIDEO RECORDER
 Model No. : DHI-NVR4232-4KS2
 Final Test Result : PASS
 Temperature : 23° C
 Relative Humidity : 52%
 Atmospheric Pressure : 100 kPa
 Test Date : Nov 06, 2016

Test Mode 1:

For EN 55024: 2010

Test Voltage: AC 230V/50Hz						
Waveform : 1.2/50µs(8/20µs) Repetition rate : 60 sec Time : 20 time/each condition						
/Phase Voltage / Mode / Polarity / Result			0°	90°	180°	270°
<u>0.5/1.0 kV</u>	L-N	+	A	A	A	A
		-	A	A	A	A
<u>1.0/2.0 kV</u>	L-PE	+	A	A	A	A
		-	A	A	A	A
<u>1.0/2.0 kV</u>	N-PE	+	A	A	A	A
		-	A	A	A	A

Waveform :10/700µs Repetition rate : 60 sec Time : 5 time/each condition				
Voltage	<u>0.5 kV</u>		<u>1.0 kV</u>	
Mode / Polarity / Result	+	-	+	-
LAN Port	A	A	A	A
POE Port	A	A	A	A



For EN 50130-4: 2011

Power Port

Test Voltage: AC 230V/50Hz						
Waveform : 1.2/50µs(8/20µs) Repetition rate : 60 sec Time : 20 time/each condition						
/Phase Voltage / Mode / Polarity / Result			0°	90°	180°	270°
<u>0.5/1.0 kV</u>	L-N	+	A	A	A	A
		-	A	A	A	A
<u>1.0/2.0 kV</u>	L-PE	+	A	A	A	A
		-	A	A	A	A
<u>1.0/2.0 kV</u>	N-PE	+	A	A	A	A
		-	A	A	A	A

Waveform : 1.2/50µs(8/20µs) Repetition rate : 60 sec Time : 5 time/each condition				
Voltage	<u>0.5 kV</u>		<u>1.0 kV</u>	
Mode / Polarity / Result	+	-	+	-
LAN Port	A	A	A	A
POE Port	A	A	A	A

Waveform : 10/700µs Repetition rate : 60 sec Time : 5 time/each condition				
Voltage	<u>0.5 kV</u>		<u>1.0 kV</u>	
Mode / Polarity / Result	+	-	+	-
LAN Port	A	A	A	A
POE Port	A	A	A	A



Power Port

Test Voltage: AC 195.5V/50Hz						
Waveform : 1.2/50µs(8/20µs) Repetition rate : 60 sec Time : 20 time/each condition						
/Phase Voltage / Mode / Polarity / Result			0°	90°	180°	270°
<u>0.5/1.0 kV</u>	L-N	+	A	A	A	A
		-	A	A	A	A
<u>1.0/2.0 kV</u>	L-PE	+	A	A	A	A
		-	A	A	A	A
<u>1.0/2.0 kV</u>	N-PE	+	A	A	A	A
		-	A	A	A	A

Waveform : 1.2/50µs(8/20µs) Repetition rate : 60 sec Time : 5 time/each condition				
Voltage	<u>0.5 kV</u>		<u>1.0 kV</u>	
Mode / Polarity / Result	+	-	+	-
LAN Port	A	A	A	A
POE Port	A	A	A	A

Waveform : 10/700µs Repetition rate : 60 sec Time : 5 time/each condition				
Voltage	<u>0.5 kV</u>		<u>1.0 kV</u>	
Mode / Polarity / Result	+	-	+	-
LAN Port	A	A	A	A
POE Port	A	A	A	A



Power Port

Test Voltage: AC 253V/50Hz						
Waveform : 1.2/50µs(8/20µs) Repetition rate : 60 sec Time : 20 time/each condition						
/Phase Voltage / Mode / Polarity / Result			0°	90°	180°	270°
<u>0.5/1.0 kV</u>	L-N	+	A	A	A	A
		-	A	A	A	A
<u>1.0/2.0 kV</u>	L-PE	+	A	A	A	A
		-	A	A	A	A
<u>1.0/2.0 kV</u>	N-PE	+	A	A	A	A
		-	A	A	A	A

Waveform : 1.2/50µs(8/20µs) Repetition rate : 60 sec Time : 5 time/each condition					
Voltage		<u>0.5 kV</u>		<u>1.0 kV</u>	
Mode / Polarity / Result		+	-	+	-
LAN Port		A	A	A	A
POE Port		A	A	A	A

Waveform : 10/700µs Repetition rate : 60 sec Time : 5 time/each condition					
Voltage		<u>0.5 kV</u>		<u>1.0 kV</u>	
Mode / Polarity / Result		+	-	+	-
LAN Port		A	A	A	A
POE Port		A	A	A	A

Test engineer: Sun. Zhang



11.6. Test Photographs





12. Conduction Disturbances induced by Radio-Frequency Fields


12.1. Test Procedure

- a. The EUT shall be operated within its intended climatic conditions. The temperature and relative humidity should be recorded.
- b. This test method test can be performed without using a sell shielded enclosure. This is because the disturbance levels applied and the geometry of the setups are not likely to radiated a high amount of energy, especially at the lower frequencies. If under certain circumstances the radiated energy is too high, a shielded enclosure has to be used.
- c. The test shall be performed with the test generator connected to each of the coupling and decoupling devices in turn while the other non-excited RF-input ports of the coupling devices are terminated by a 50 ohm load resistor.
- d. The frequency range is swept from 150 KHz to 80 MHz, using the signal levels established during the setting process, and with the disturbance signal 80% amplitude modulated with a 1KHz sign wave, pausing to adjust the RF-signal level or to switch coupling devices as necessary. The rate of sweep shall no exceed 1.5×10^{-3} decades/s. Where the frequency is swept incrementally, the step size shall no exceed 1% of the start and thereafter 1% of the preceding frequency value.
- e. The dwell time at each frequency shall not be less than the time necessary for the EUT to be exercised, and able to respond. Sensitive frequencies e.g. clock frequency (ies) and harmonics or frequencies of dominant interest shall be analyzed separately.
- f. An alternative test procedure may be adopted, wherein the frequency range is swept incrementally, with a step size not exceeding 4% of the start ad thereafter 4% of the preceding frequency value. The test level should be at least twice the value of the specified test level.
- g. In cases of dispute, the test procedure using a step size not exceeding 1% of the start and thereafter 1% of preceding frequency value shall take precedence.
- h. Attempts should be made to fully exercise the EUT during testing, and to fully interrogate all exercise modes selected for susceptibility.
- i. The use of special exercising programs is recommended.
- j. Testing shall be performed according to a Test Plan, which shall be included in the test report.
- k. It may be necessary to carry out some investigatory testing in order to establish some aspects of the test plan.

12.2. Test Severity Levels

Level	Voltage Level (e.m.f.)
1	1 V
2	3 V
3	10 V
x	Specified
NOTE - x is an open class. This level can be specified in the product specification.	

12.3. TEST SETUP



- Note:**
1. The EUT is setup 0.1m above Ground Reference Plane
 2. The CDNs and / or EM clamp used for real test depends on ports and cables configuration of EUT.
 3. For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

12.4. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
Conducted immunity test system	FRANKONIA	CIT-10/75	102D1294	2016.03.26	2017.03.25
EM Injection clamp	FCC	F-203I-23MM	536	2016.03.26	2017.03.25
CDN	FRANKONIA	CDN-T2	A3010029	2016.03.26	2017.03.25
CDN	FRANKONIA	CDN-T4	A3015017	2016.03.26	2017.03.25
CDN	FRANKONIA	CDN-T8	A3022010	2016.03.26	2017.03.25
CDN	FRANKONIA	CDN-M2	A3002037	2016.03.26	2017.03.25
CDN	FRANKONIA	CDN-M2+M3	A3011102	2016.03.26	2017.03.25
CDN	FCC	CDN-M5/32	A3013024	2016.03.26	2017.03.25
6 dB Attenuator	FRANKONIA	N/A	N/A	2016.03.26	2017.03.25
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-005	2016.03.29	2017.03.28
EN61000-4-6	Hubert GmbH	Ver 2.21	N/A	N/A	N/A



12.5. Test Result and Data

Basic Standard : IEC 61000-4-6
 Product Standard : EN 50130-4: 2011
 Product Standard : EN 55024 : 2010
 Equipment : NETWORK VIDEO RECORDER
 Model No. : DHI-NVR4232-4KS2
 Final Test Result : PASS
 Temperature : 23° C
 Relative Humidity : 52%
 Atmospheric Pressure : 100 kPa
 Test Date : Nov 06, 2016

Test Mode 1:

For EN 55024: 2010

Test Voltage: AC 230V/50Hz

Frequency : 0.15~100MHz, Modulation : AM 80%,1KHz sine wave, Dwell time: 3.0s Frequency Step Size : 1 % of preceding frequency value			
Frequency	Test mode	Voltage(V)	Result
0.15 ~ 80MHz	Power(M3)	3	A
0.15 ~ 80MHz	LAN Port	3	A
0.15 ~ 80MHz	POE Port	3	A

Test Mode 1

For EN 50130-4: 2011

Test Voltage: AC 230V/50Hz

Frequency : 0.15~100MHz, Modulation : AM 80%,1KHz sine wave, Dwell time: 3.0s Frequency Step Size : 1 % of preceding frequency value			
Frequency	Test mode	Voltage(V)	Result
0.15 ~ 100MHz	Power(M3)	10	A
0.15 ~ 100MHz	LAN Port	10	A
0.15 ~ 100MHz	POE Port	10	A



Test Voltage: AC 195.5V/50Hz

Frequency : 0.15~100MHz, Modulation : AM 80%,1KHz sine wave, Dwell time: 3.0s			
Frequency Step Size : 1 % of preceding frequency value			
Frequency	Test mode	Voltage(V)	Result
0.15 ~ 100MHz	Power(M3)	10	A
0.15 ~ 100MHz	LAN Port	10	A
0.15 ~ 100MHz	POE Port	10	A

Test Voltage: AC 253V/50Hz

Frequency : 0.15~100MHz, Modulation : AM 80%,1KHz sine wave, Dwell time: 3.0s			
Frequency Step Size : 1 % of preceding frequency value			
Frequency	Test mode	Voltage(V)	Result
0.15 ~ 100MHz	Power(M3)	10	A
0.15 ~ 100MHz	LAN Port	10	A
0.15 ~ 100MHz	POE Port	10	A

Test engineer: Sun. Zhang




12.6. Test Photographs



13. Power Frequency Magnetic Field Immunity Test

13.1. Test Setup



- GPR : Ground plane
- A : Safety earth
- S : Insulating support
- EUT : Equipment under test
- Lc : Induction coil
- E : Earth terminal
- C1 : Power supply circuit
- C2 : Signal circuit
- L : Communication line
- B : To power supply source
- D : To signal source, simulator
- G : To the test generator

13.2. Test Severity Levels

Level	Magnetic field strength (A/m)
1	1
2	3
3	10
4	30
5	100
X ¹⁾	special

NOTE 1 "X" is an open level. This level can be given in the product specification.

13.3. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
TRANSIENT	EMCPARTNER	TRA2000IN6	901	2016.03.26	2017.03.25
H-Filed-Loop	EMCPARTNER	MF1000-1	144	2016.03.26	2017.03.25
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-005	2016.03.29	2017.03.28



13.4. Test Result and Data

Basic Standard : IEC 61000-4-8
Product Standard : EN 55024 : 2010
Equipment : NETWORK VIDEO RECORDER
Model No. : DHI-NVR4232-4KS2
Final Test Result : PASS
Temperature : 23° C
Relative Humidity : 52%
Atmospheric Pressure : 100 kPa
Test Date : Nov 06, 2016

Mode 1

Power Frequency Magnetic Field : <u>50/60</u> Hz, <u>1</u> A/m		
Coil Orientation	Testing duration	Results
X-axis	1.0 Min	A
Y-axis	1.0 Min	A
Z-axis	1.0 Min	A

Test engineer: Sun. Zhang



13.5. Test Photographs






14. Voltage Dips and Voltage Interruptions Immunity Test Setup

14.1. Test Conditions

1. Source voltage and frequency : AC 100/230/240V / 50Hz, Single phase.
2. Test of interval : 10 sec.
3. Level and duration : Sequence of 3 dips/interrupts.
4. Voltage rise (and fall) time : 1 ~ 5 μ s.
5. Test severity :

Voltage dips and Interrupt reduction (%)	Test Duration (period)
>95%	250
30%	25
>95%	0.5

14.2. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

14.3. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
TRANSIENT	EMCPARTNER	TRA2000IN6	901	2016.03.26	2017.03.25
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-005	2016.03.29	2017.03.28



14.4. Test Result and Data

Basic Standard : IEC 61000-4-11
 Product Standard : EN 50130-4: 2011
 Product Standard : EN 55024 : 2010
 Equipment : NETWORK VIDEO RECORDER
 Model No. : DHI-NVR4232-4KS2
 Final Test Result : PASS
 Temperature : 23° C
 Relative Humidity : 52%
 Atmospheric Pressure : 100 kPa
 Test Date : Nov 06, 2016

Test Mode 1
 For EN 55024: 2010

Voltage(UT): AC 100V/50 Hz Interval(s) : 10s Times : 3										
Test mod	Test level UT %	Durations (period / ms)	Phase / Result							
			0	45	90	135	180	225	270	315
Voltage interruptions	>95%	250	C	C	C	C	C	C	C	C
Voltage dips	30%	25	B	B	B	B	B	B	B	B
	>95%	0.5	B	B	B	B	B	B	B	B

Voltage(UT): AC 230V/240 V/50 Hz Interval(s) : 10s Times : 3										
Test mod	Test level UT %	Durations (period / ms)	Phase / Result							
			0	45	90	135	180	225	270	315
Voltage interruptions	>95%	250	C	C	C	C	C	C	C	C
Voltage dips	30%	25	B	B	B	B	B	B	B	B
	>95%	0.5	B	B	B	B	B	B	B	B



For EN 50130-4: 2011

Test Voltage: AC 230V/50Hz Interval(s) : 10s Times : 3										
Test mod	Test level UT %	Durations (period / ms)	Phase / Result							
			0	45	90	135	180	225	270	315
Voltage interruptions	100%	250	A	A	A	A	A	A	A	A
Voltage dips	20%	250	A	A	A	A	A	A	A	A
	30%	25	A	A	A	A	A	A	A	A
	60%	10	A	A	A	A	A	A	A	A

100% and 20% is permitted to UPS to meet the requirements of Result A.

Test Voltage: AC 195.5V/50Hz Interval(s) : 10s Times : 3										
Test mod	Test level UT %	Durations (period / ms)	Phase / Result							
			0	45	90	135	180	225	270	315
Voltage interruptions	100%	250	A	A	A	A	A	A	A	A
Voltage dips	20%	250	A	A	A	A	A	A	A	A
	30%	25	A	A	A	A	A	A	A	A
	60%	10	A	A	A	A	A	A	A	A

100% and 20% is permitted to UPS to meet the requirements of Result A.



Test Voltage: AC 253V/50Hz Interval(s) : 10s Times : 3										
Test mod	Test level UT %	Durations (period / ms)	Phase / Result							
			0	45	90	135	180	225	270	315
Voltage interruptions	100%	250	A	A	A	A	A	A	A	A
Voltage dips	20%	250	A	A	A	A	A	A	A	A
	30%	25	A	A	A	A	A	A	A	A
	60%	10	A	A	A	A	A	A	A	A

100% and 20% is permitted to UPS to meet the requirements of Result A.

Test engineer: Sun. Zhang



14.5. Test Photographs





15. EUT Photographs

1) EUT Photo



2) EUT Photo





3) EUT Photo



4) EUT Photo





5) EUT Photo



6) EUT Photo





7) EUT Photo



8) EUT Photo

