



EVPÜ[®]

NOTIFIED BODY No. 1293

CERTIFICATE OF CONSTANCY OF PERFORMANCE

No. 1293 – CPR – 0703

In compliance with the *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

Intelligent analogue addressable electrical mains switching output module with built-in isolator SensoIRIS MOUT-240, Belinda MOUT-240, Erida MOUT-240, Marl MOUT-240, Smoke sense MOUT-240, SensoIRIS MOUT-240 IP55, Expera Oi Mains IP55, MAGPRO-R

For specifications see Annex to this certificate placed on the market under the name or trade mark of

**Teletek Electronics JSC
14A Srebarna Str., 1407 Sofia, Bulgaria**

and produced in the manufacturing plant

**Teletek Electronics JSC
14A Srebarna Str., 1407 Sofia, Bulgaria**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard

**EN 54-18:2005
EN 54-18:2005/AC:2007
EN 54-17:2005
EN 54-17:2005/AC:2007**

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on October 28th, 2020 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Nová Dubnica, October 28th, 2020

053751




Marek Hudák
Director NB

Annex to Certificate No. 1293 - CPR – 0703 from October 28th, 2020

Technical Specifications

SensolRIS MOUT-240 (derived variants Belinda MOUT-240, Erida MOUT-240, Marl MOUT-240, Smoke sense MOUT-240, SensolRIS MOUT-240 IP55, Expera Oi Mains IP55, MAGPRO-R) is an electrical mains switching relay output control module designed for application in addressable fire alarm systems, supporting communication protocol.

SensolRIS MOUT-240, Belinda MOUT-240, Erida MOUT-240, Marl MOUT-240, Smoke sense MOUT-240 is mounted in a separate small plastic box suitable for wall mounting, with transparent cover for visual inspection.

SensolRIS MOUT-240 IP55, Expera Oi Mains IP55, MAGPRO-R is mounted in a separate plastic box suitable for wall mounting and IP55 protection.

The device works with Operating voltage (16 – 32) VDC.

Essential characteristics	Harmonised technical specification		Performance
	EN 54-18:2005 EN 54-18:2005/ AC:2007	EN 54-17:2005 EN 54-17:2005/ AC:2007	
Response delay (response time)	cl. 5.2	---	Pass
Performance under fire conditions	cl. 5.1.4	cl. 5.2	Pass
Operational reliability	cl. 5.1.4	cl. 4	Pass
Durability of operational reliability: temperature resistance	cl. 5.3, 5.4	cl. 5.4, 5.5	Pass
Durability of operational reliability: vibration resistance	cl. 5.8 to 5.11	cl. 5.9 to 5.12	Pass
Durability of operational reliability: humidity resistance	cl. 5.5, 5.6	cl. 5.6, 5.7	Pass
Durability of operational reliability: corrosion resistance	cl. 5.7	cl. 5.8	Pass
Durability of operational reliability: electrical stability	cl. 5.2, 5.12	cl. 5.3, 5.13	Pass

Nová Dubnica, October 28th, 2020



Marek H u d á k
Director NB