



IPC-HFW3441T-ZAS-S2

Tubular IP H265 4M DN WDR Starlight IVS SMD IR60m 2.7-13.5VFM IP67 PoE SD AUDIO MIC E/S AI



Características

- Resolución hasta 4MP@25IPS.
 - Óptica motorizada 2.7-13.5mm (104°-29°x54°-16°x125°-33° (HxVxD)). F1.5.
 - 1E/1S Alarma, 1E/1S Audio, Micro integrado.
 - Compatible con: ONVIF (Profile S/Profile G/Profile T); CGI; P2P; Milestone; Genetec.
 - Software de gestión: Smart PSS, DSS, DMSS.
 - Alimentación 12Vdc (2.8W) y PoE (3.6W). Tecnología Starlight.
 - Dimensiones y peso: 244.1x79x75.9mm / 0.82Kg.
- *WizSense Series: Perimeter Protection, Smart Search, SMD 4.0, AI SSA, Quick Pick.

Accesorios

[PFA130-E](#)
[PFA135](#)



IPC-HFW3441T-ZAS-S2

Tubular IP H265 4M DN WDR Starlight IVS SMD IR60m 2.7-13.5VFM IP67 PoE SD AUDIO MIC E/S AI

Especificaciones de Producto

| | |
|--------------------------|---|
| SENSOR | 1/3" CMOS 4MP |
| MAX. RESOLUCIÓN / IPS | 4MP@25IPS |
| CONMUTACIÓN | Día - Noche con Filtro ICR |
| MIN. ILUMINACIÓN | 0.005Lux@F1.5 |
| ÓPTICA | Varifocal Motorizada 2.7-13.5mm |
| LEDs IR | LEDS IR (Hasta 60m) |
| COMPRESIÓN (VÍDEO/AUDIO) | H.265/H.264/H.264B/H.264H/MJPEG (Sub Stream) y G.711a/G.711Mu/G.726/G.723 |
| FUNCIONES DE CÁMARA | WDR(120dB), 3DNR, HLC, BLC |
| STREAM DE VÍDEO | Main 4MP@25IPS / 2nd D1 / 3rd 720@25IPS |
| INTERFAZ AUXILIAR | Micro SD (jusqu'à 256 Go) |
| ALIMENTACIÓN / CONSUMO | 12Vdc et PoE |
| TEMPERATURA | De -30°C a +60°C (95% HR) |
| PROTECCIÓN | IP67 |
| AI | WizSense Series |
| IVS Analytics | Tripwire et Intrusion. |
| SOPORTA SMD | SMD 4.0 |

<https://www.ibdglobal.com/shop/product/ipc-hfw3441t-zas-s2-tubular-ip-h265-4m-dn-wdr-starlight-ivs-smd-ir60m-2-7-13-5vfm-ip67-poe-sd-audio-mic-e-s-ai-17440>