

DC116

Contacto magnético para superficie, terminal de tornillos. Apertura operativa máx. 36mm.

Industrial Surface Mount Contact

The DC116 series features a wider make distance and works better on steel without time-consuming installation of brackets. A wider break distance helps prevent false alarms caused by loose fitting doors.

Applications

The contacts are used to protect openings such as metal entry/exit doors, overhead doors, roof hatches or hinged skylights.



Detalles

- Rugged design for industrial applications
- Models for use on steel without time-consuming brackets
- Concealed terminals resist tampering and inadvertent shorting
- Easy clamping terminals speed installation
- Mounting screws included

DC116

Contacto magnético para superficie, terminal de tornillos. Apertura operativa máx. 36mm.

Technical specifications

General

Tipo de Aplicación	Montaje en Superficie
Tipo de contacto	NC
Conectividad	Screw

Wired/wireless

Wired-wireless	Cableado
Brecha de funcionamiento	31 mm (max.)

Physical

Dimensiones físicas	99 x 17 x 15 mm
Colour	Beige



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 5 May 2023 - 9:33