

DHL49-4K

49" UHD LCD Monitor



Features:

- 4K Ultra-HD resolution
- Industrial level LCD panel, suitable for continuous 24/7 operation
- Built-in 3D COMB filter and 3D noise reduction
- 8ms fast response time for no motion blur, judder or ghosting
- High fidelity digital processing for a brilliant and vivid video
- Brightness smart detection, power-saving
- Using tamper-proof metal housing
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption, ultra-quiet
- Wide array of connectivity options HDMI, DVI, VGA, BNC, USB, RS232



Technical Specification

Model

Model	DHL49-4K
-------	----------

Display

Screen Size	48.5"
Aspect Ratio	16:9
Resolution	3840×2160 (UHD)
Backlight	LED
Brightness/Luminance	500 cd/㎡
Contrast	1100:1
Display Color	16.7M(8bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response time	8ms
Refresh Rate	60Hz

Signals

Input	VGA(D-Sub)×1, CVBS(BNC)×1, DVI-D×1, HDMI×2, RS232×1, USB multimedia×1
Output	Audio×1, RS232×1
	Speaker 10W×2

General

Power Supply	AC100~240V (+/-10%), 50/60 Hz
--------------	-------------------------------

Consumption (Standard)	70W	
Consumption (Standby)	≤1W	
Type	Internal	
Net Weight	18kg (39.7lb)	
Gross Weight	24.5kg (54.0lb)	
Bezel Width	25.5mm (U/L/R/B)	
Wall Mount	3.9300×300mm (11.8"×11.8")	
Dimension without standard (W×H×D)	1127.1×667.3×51.9mm (44.4"×26.3"×2.0")	
Package(W×H×D)	1272×826×210mm (50.1"×32.5"×8.3")	
Work Environment	Temperature	0 C~50 C (32°F~122°F)
	Humidity	20%~90%

Accessory

Standard	VGA cable, power cable
Optional	Pedestal, hanging bracket

Certifications

Certifications	CE/FCC
----------------	--------

Dimensions(mm)

