

# IR FIXED LENS DOME CAMERA

DI-350IP5S36



1/3" CMOS Sensor  
5 Mega-Pixel  
True Day & Night (IR Cut Removable)  
H.265 (HEVC) Compression  
0 Lux (IR On) Min. Illumination

ONVIF  
D-WDR / BLC / HLC  
3D Noise Reduction  
Motion Detection and Privacy Masking  
Analytics Support

3.6mm Mega-Pixel Lens  
15m IR Illumination  
PoE Support  
IP 66 Protection

## Specifications

Camera	Video	Model	DI-350IP5S36
		Image Sensor	1/3" CMOS (4:3)
		Effective Pixels	2592x1944
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	5MP - 1-20FPS / 4MP and lower: 1-25/30FPS
		Day & Night	ICR
	Audio	Min. Illumination	Day: 0.045lux / Night: 0.01lux (@F1.8, AGC On) 0lux with IR on
		Audio compression	No
	Image Processing	Communication	No
		Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
		Image Enhancement	BLC, HLC, Digital WDR, ROI
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip/Corridor Mode
		Privacy Zone	Yes
		Motion Detection	Yes
Compression	Analytics	Camera Tampering, Line Crossing, Sterile Area	
	Video Compression	H.265 / H.264 / MJPEG (Sub-Streams Only)	
	Resolutions	5MP (2592x1944) / 4MP (2592x1520) / (2560x1440) / 3MP(2304x1296) / 2MP (1920x1080) / 1MP (1280x720) / D1 (704x576) / CIF (352x288)	
	Multi-Stream	Master Stream: 5MP(1~20fps) / 4MP/3MP/2MP/1MP(1~30fps) Sub-Stream: 1MP/D1/CIF(1~30fps),Third-Stream: QVGA/D1/CIF(1~30fps)	
	Bit rate	64Kbps ~ 8Mbps@H.265 / 64Kbps ~ 8Mbps@H.264	
	Encode Mode	VBR/CBR	
	Image Quality	Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	15m (2 High Power IR LED)
	Lens (Field of View)	3.6mm (79.4°)
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66
	Bracket	3-Axis Wall Bracket
Connectivity	Dimensions	Ø107mm×95mm
	Weight(gross)	400g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	No
	Mic Connectivity	No
	SD Card	No
Network	RS485	No
	Alarm	No
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
Others	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP
	ONVIF	Yes
	Ethernet	100Mbps
	PoE	Yes
	Power Supply	DC12V/~280mA / PoE/~4W
	Work Environment	-30°C~50°C, 10%~90% Humidity

