


IR MOTORIZED VF DOME CAMERA

DI-350IP5SMVF



1/3" CMOS Sensor
 5 Mega-Pixel
 True Day & Night (IR Cut Removable)
 H.265 (HEVC) Compression
 0 Lux (IR On) Min. Illumination

ONVIF
 D-WDR / BLC / HLC
 3D Noise Reduction
 Motion Detection and Privacy Masking
 Analytics Support

3.3-12mm Motorized Lens with Auto-Focus
 25m IR Illumination
 PoE Support
 IP 66 Protection

Specifications

Camera	Video	Model	DI-350IP5SMVF
		Image Sensor	1/3" CMOS (4:3)
		Effective Pixels	2592x1944
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	5MP - 1-20FPS / 4MP and lower: 1-25/30FPS
		Day & Night	ICR
	Audio	Audio compression	No
		Communication	No
		Image Processing	Image Settings
	Image Enhancement		BLC, HLC, Digital WDR, ROI
	Noise Reduction		3D-DNR
	Image Orientation		Mirror/Flip/Corridor Mode
	Privacy Zone		Yes
	Motion Detection		Yes
	Compression	Analytics	Camera Tampering, Line Crossing, Sterile Area
Video Compression		H.265 / H.264 / MJPEG (Sub-Streams Only)	
Resolutions		5MP (2592x1944) / 4MP (2592x1520) / (2560x1440) / 3MP(2304x1296) / 2MP (1920x1080) / 1MP (1280x720) / D1 (704x576) / CIF (352x288)	
Multi-Stream		Master Stream: 5MP(1~20fps) / 4MP/3MP/2MP/1MP(1~30fps) Sub-Stream: 1MP/D1/CIF(1~30fps),Third-Stream: QVGA/D1/CIF(1~30fps)	
Bit rate		64Kbps ~ 8Mbps@H.265 / 64Kbps ~ 8Mbps@H.264	
Encode Mode		VBR/CBR	
	Image Quality	Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	25m (2 High Power IR LED)
	Lens (Field of View)	3.3-12mm Motorized with Auto Focus (81.2°-31.8°)
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66
	Bracket	3-Axis Wall Bracket
Connectivity	Dimensions	Ø120mm×100mm
	Weight(gross)	400g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	No
	Mic Connectivity	No
Network	SD Card	No
	RS485	No
	Alarm	No
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP
Others	ONVIF	Yes
	Ethernet	100Mbps
	PoE	Yes
	Power Supply	DC12V/~280mA / PoE/~4W
	Work Environment	-30°C~50°C, 10%~90% Humidity

