

FE240

Retenedor electromagnético de 400N para montaje empotrado.

General

The FE240 is a flush mount door holder, with a Bayblend housing, which offers a 400N holding force.

Magnet construction

The magnet is constructed with a pressed coil and anti-remenance pin, giving it a protection of IP54. The protection diodes are integrated into this construction.

Housing

The plastic housing is manufactured from Bayblend and contains 30% PA6 glass fiber, which makes it much stronger than standard ABS. Bayblend offers high heat resistance, high impact and notched impact strength, and high stiffness and dimensional stability.

Installer friendly

- For practical ease of installation, the door holder comes complete with electrical screw terminals.
- The housing is predrilled in a practical, standard format for rapid mounting.
- The door holder is supplied complete with a keeper plate, which offer angular adjustment.

Approvals

The FE240 is fully approved according to EN1155.



Details

- Low power - 1.6 W
- 400 N holding force
- Anti-remnant ejector
- Spark suppression diode and reverse polarity protection
- EN1155 approved
- Keeper plate included

FE240

Retenedor electromagnético de 400N para montaje empotrado.

Technical specifications

General

Botón de liberación	No
---------------------	----

Electrical

Tipo de fuente de alimentación	24 VCC
--------------------------------	--------



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 5 January 2023 - 15:53