

## 5+5MP Indoor Wi-Fi Dual-Lens Pan & Tilt Camera

# DH-HPT1539DD-STW-5E2



#### **Series Overview**

The Hero Dual Series, part of the Dahua Wireless series, has both fixed and PT lenses, allowing for simultaneous live monitoring of two areas with just one camera for multi-angle coverage. Both lenses offer AI human & pet detection, which significantly reduce the occurrence of false alarms. Particularly, the PT lens can identify moving targets and track them automatically. When the camera detects an intruder, it will trigger sound and light alerts and send notifications to the mobile client, keeping you up to date regardless of your location. These cameras are commonly used in such small-scale scenarios as stores and restaurants.





**Micro SD Card** Low-cost storage

intruders

Sound and Light Alarm

Provides instant alarms to deter



regularly



**One-click Privacy Mode** Protects your privacy



**Bluetooth Pairing** Fast pairing with Bluetooth



### **Abnormal Sound Alarm**

Accurately detects abnormal sounds and sends alarm information

**Dual-Band Wi-Fi 6** 

The perfect integration of speed and anti-interference.

# **Upgrade Your Experience with DMSS**

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.







# Specifications

1/3" CMOS

2 (IR LED)

0° to 15°

Fixed-focal

1/3" CMOS 2880 (H) × 1620 (V)

3.6 mm F2.0

2880 (H) × 1620 (V)

Up to 30 m (98.43 ft) (IR)

H: 86°; V: 46°; D: 104°

Up to 30 m (98.43 ft) (IR) Up to 30 m (98.43 ft) (Warm light)

2 (IR LED); 1 (Warm light)

H: 86°; V: 46°; D: 104°

Pan: 0° to 349° Tilt: -5° to 90°

Fixed-focal

3.6 mm F2.0

### Camera

Fixed Lens Image Sensor Max. Resolution Illumination Distance Illuminator Number Angle Adjustment Lens Type Focal Length Max. Aperture Field of View

#### PT Lens

Image Sensor Max. Resolution Illumination Distance Illuminator Number Angle Adjustment Lens Type Focal Length Max. Aperture Field of View

### Intelligence

Human Detection Pet Detection Yes Yes

# What's in the box



#### Tools: Installation Position

Map×1 Screw Package×1 Bracket×1

#### Documents: QR Code×1

Power:

Power Adapter×1

Power Cord×1

Quick Start Guide×1 Legal and regulation information×1

### **Audio and Video**

Video Compression	H.265
Video Frame Rate	Main stream: 2880 × 1620@15 fps sub stream: 640 × 360@15 fps *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.
Video Bit Rate	H.265: 768 kbps-4096 kbps
Day/Night	Auto(ICR)/Color/B/W
WDR	DWDR
Motion Detection	Yes
Image Rotation	0°/180°
Built-in MIC	Yes, built-in Mic
Built-in Speaker	Yes, built-in speaker
Audio Compression	G.711a
Network	
Network Port	RJ-45 (10/100 Base-T)
Wi-Fi	IEEE 802.11a/b/g/n/ac/ax 2.4–2.4835 GHz, 2.4 G, EIRP≤20 dBm & 5.15–5.25 GHz, 5 G, EIRP≤23 dBm@5150–5250 MHz
Wi-Fi Pairing	Bluetooth pairing
Storage	Micro SD card (support max. 256 GB)
Management Software	DMSS
Mobile Client	iOS;Android
Function	
Abnormal Sound Alarm	Yes
Privacy Mode	Yes
General	
Certifications	CE
Power Supply	5 VDC
Power Consumption	Basic: 2.5 W; Max.: 5.4 W (pulling stream+ IR + PT rotation)
Operating Temperature	-10 °C to +45 °C (-4 °F to +113 °F)
Operating Humidity	≤95% (RH), non-condensing
Casing Material	Plastic
Product Dimensions	Φ80.9 mm × 125.7mm (3.19" × Φ4.95")
Net Weight	233 g (0.51 lb)