

# DH-PFS3008-8GT-L

## 8-Port Desktop Gigabit Ethernet Switch



- Compact design: Miniature size and light weight make it easy to deploy
- Plug and play: No configuration required
- Green technology: Adopts high quality environmentally friendly plastics
- 7x24H: Stable performance for long-term operation

### System Overview

8 × 10/100/1000 Mbps adaptive ports, highly integrated design, compact, portable, easy to operate, suitable for small and medium office and home networks.

### Technical Specification

#### Performance

Layer Layer 2

Managed No

#### Hardware

Standard Power Supply Yes

PoE No

Ethernet Port 8

Ethernet Port Rate 1 Gbps

Power Supply 5V/1A DC

Operating Temperature -10°C to 55°C (14°F to 131°F)

Operating Humidity 10%–90%

Storage Temperature -40°C to 70°C (-40°F to 158°F)

Storage Humidity 10%–90%

Power Consumption Idling: 0.81W  
Full load: 4W

#### Performance

Switching Capacity 16 Gbps

Packet Forwarding Rate 11.9 Mpps

Packet Buffer Memory 1.5 Mbits

MAC Table Size 2K

Standards Compliance IEEE 802.3i, IEEE 802.3u, IEEE802.3ab, IEEE802.3x

### Application

The product is applicable to small and medium office and home networks.

### General

ESD	Air discharge: 8kV Contact discharge: 4kV
Thunderproof	Common mode: 2kV
Net Weight	0.11 kg (0.24 lb)
Gross Weight	0.22 kg (0.49 lb)
Dimensions	125 mm × 65 mm × 22 mm (4.92" × 2.56" × 0.87" )
Packaging Dimensions	128 mm × 77 mm × 78 mm (5.04" × 3.03" × 3.07" )

### Dimensions (mm[inch])

