

# FAW355WC

**Piloto convencional estroboscópico a 24Vcc para pared. Blanco con lente transparente. IP65. Base alta para tubo vista.**

## General

---

The FAW355W is a general purpose wall mount LED beacon for fire alarm applications. It features a special deep base containing all wiring connections and allow for easy removal/placement of the device. With an EN54-23 approved coverage pattern of W-3.1-11.3, each FAW355WC may be mounted up to 3.5m high and cover a square room of 11.3 x 11.3m with a single device.

## Easy and Fast Installation

---

The FAX350 beacons allow faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws, these beacons use a deep base version of the TimeSaver™ bases from the 630 series detectors. Heads are simply locked onto the base with a “twist and click” action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are naturally reduced as well.

## Efficient and versatile

---

The FAX350 beacons utilise a specially designed lens giving a uniformed light output over the specified coverage area. The flash rate of the beacon may be adjusted during installation, with a selection of 0.5Hz or 1Hz.

The mechanism for locking the device to the base may be activated if required. Once activated, a special tool is required to remove the beacon from the base.



## Details

---

- Automatic synchronisation
- Anti-Tamper locking mechanism
- Deep mounting base
- Wiring directly to base
- Flash rate selectable
- IP65 Ingress protection

# FAW355WC

Piloto convencional estroboscópico a 24Vcc para pared. Blanco con lente transparente. IP65. Base alta para tubo vista.

## Technical specifications

### Eléctrico

Voltaje de funcionamiento 17 to 60 VDC

### Físico

Dimensiones físicas 100 x 104 mm (Ø x D)  
Peso neto 250 g  
Color Blanco  
Tipo de Montaje Montaje en pared  
Altura de montaje up to 3.1 m  
Material Policarbonato de alto impacto

### Medioambiental

Temperatura de funcionamiento -25 to +70°C  
Humedad relativa 5 to 95% noncondensing  
Entorno Interior, Exterior  
Clasificación IP IP65

### Regulatory

Certificación EN54-23

### Operation

Continuous

### Current consumption

20mA @ 0.5 Hz / 40mA @ 1 Hz

### Flash rate

0.5Hz or 1Hz

### Automatic synchronisation

Phased start

### Line monitoring input

Polarised input


### Flash colour

White

### EN54-23 rating

Light coverage W-3.1-11.3  
Floor coverage up to 11.3m x 11.3m

### EN54-23 Coverage: W-3.5-11.5



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de [es.firesecurityproducts.com](http://es.firesecurityproducts.com) o póngase en contacto con su comercial.

Last updated on 5 January 2023 - 15:52