

30M IR VARI-FOCAL BULLET CAMERA

I3-350IP5SVF



1/3" CMOS Sensor
 5 Mega-Pixel
 True Day & Night (IR Cut Removable)
 H.265 (HEVC) Compression
 0 Lux (IR On) Min. Illumination

ONVIF
 D-WDR / BLC / HLC
 3D Noise Reduction
 Motion Detection and Privacy Masking
 Analytics Support

3-11mm Mega-Pixel Lens
 30m IR Illumination
 PoE Support
 IP 66 Protection

Specifications

Camera	Video	Model	I3-350IP5SVF
		Image Sensor	1/3" CMOS (4:3)
		Effective Pixels	2592x1944
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	5MP - 1-20FPS / 4MP and lower: 1-25/30FPS
		Day & Night	ICR
	Audio	Min. Illumination	Day: 0.045lux / Night: 0.01lux (@F1.8, AGC On) 0lux with IR on
		Audio compression	No
	Image Processing	Communication	No
		Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
		Image Enhancement	BLC, HLC, Digital WDR, ROI
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip/Corridor Mode
		Privacy Zone	Yes
		Motion Detection	Yes
		Analytics	Camera Tampering, Line Crossing, Sterile Area
	Compression	Video Compression	H.265 / H.264 / MJPEG (Sub-Streams Only)
		Resolutions	5MP (2592x1944) / 4MP (2592x1520) / (2560x1440) / 3MP(2304x1296) / 2MP (1920x1080) / 1MP (1280x720) / D1 (704x576) / CIF (352x288)
Multi-Stream		Master Stream: 5MP(1~20fps) / 4MP/3MP/2MP/1MP(1~30fps) Sub-Stream: 1MP/D1/CIF(1~30fps),Third-Stream: QVGA/D1/CIF(1~30fps)	
Bit rate		64Kbps ~ 8Mbps@H.265 / 64Kbps ~ 8Mbps@H.264	
Encode Mode		VBR/CBR	
Image Quality		Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	30m (36 IR LED)
	Lens (Field of View)	3-11mm (81.2°-31.8°)
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66
	Bracket	3-Axis Wall Bracket
Connectivity	Dimensions	Φ87mm×219mm
	Weight(gross)	635g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	No
	Mic Connectivity	No
Network	SD Card	No
	RS485	No
	Alarm	No
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP
Others	ONVIF	Yes
	Ethernet	100Mbps
	PoE	Yes
	Power Supply	DC12V/~500mA / PoE/~6.5W
Work Environment	-30°C~50°C, 10%~90% Humidity	

