

4MP Compact Wi-Fi & PoE Camera

DH-IPC-K1430K-STW



Series Overview

The Cube Series, which is under the Dahua Wireless series, are cameras that are not only easy to install and operate, but also perform outstandingly and are cost-effective. They capture sharp, detailed images of scenes in high definition and offer powerful functions including AI human detection, privacy mode, and two-way talk. Information is synchronously sent to your phone to keep you up-to-date. These cameras are widely used in small and medium-sized settings such as small-sized retail stores.



4MP

Clear images with sharp details



Al Human Detection

Focuses on what matters and reduces false alarms



Wi-Fi & PoE Integration

Flexible power delivery & robust network stability



Bluetooth Pairing

Fast pairing with Bluetooth



Day&Night

Clear images even at night



Al Vehicle Detection

Focuses on what matters and reduces false alarms



WEB

Effortlessly handles device management and configuration



Micro SD Card

Low-cost storage



Al Chip

Smart algorithms, enhanced detection accuracy



Two-way Talk

Communication anytime, anywhere



H.265

Advanced H.265 compression technology



Upgrade Your Experience with DMSS

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.











Specifications

Camera

Image Sensor 1/3" CMOS

Max. Resolution 2560 (H) × 1440 (V)

Illumination Distance Up to 30 m (98.43 ft) (IR)

Illuminator Number 1 (IR LED)

Pan: 0° to 360° Tilt:-10° to 100° Angle Adjustment

Fixed-focal Lens Type

Focal Length 2.8 mm; 3.6 mm

Max. Aperture

2.8 mm: H: 92°; V: 50°; D: 107° 3.6 mm: H: 75°; V: 41°; D: 88° Field of View

Intelligence

Video Frame Rate

Human Detection Yes

Audio and Video

H.265; H.264; H.264H; H.264B; MJPEG (Only Video Compression

supported by the sub stream)

Main stream: $2560 \times 1440@(1-25/30 \text{ fps})$ Sub stream: $640 \times 360@(1-25/30 \text{ fps})$ *The values above are the max. frame rates of each

stream; for multiple streams, the values will be

subjected to the total encoding capacity.

H.264: 24 kbps-6144 kbps H.265: 9 kbps-6144 kbps Video Bit Rate

Day/Night Auto(ICR)/Color/B/W

WDR

Motion Detection OFF/ON (4 areas, rectangular)

0°/180° Image Rotation

Built-in MIC Yes, built-in Mic Built-in Speaker Yes, built-in speaker

Audio Compression PCM; G.711a; G.711Mu

Network

Network Port RJ-45 (10/100 Base-T)

Wi-Fi IEEE 802.11b/g/n/ax 2.412-2.472 GHz, 2.4 G

Wi-Fi Pairing Bluetooth pairing

Storage Micro SD card (support max. 256 GB)

Management Software Smart PSS Lite; DMSS

Mobile Client iOS;Android

Function

Abnormal Sound Alarm Yes

General

Certifications CE

Power Supply 12 VDC/PoE

Basic: 2.04 W (12 VDC); 4.7 W (PoE) Power Consumption Max.: 2.89 W (12 VDC); 5.85 W (PoE) -10 °C to +45 °C (+14 °F to +113 °F) Operating Temperature

Operating Humidity ≤95% (RH), non-condensing

Camera Button Reset button

Casing Material

64 mm × 100 mm × 34 mm (2.52" × 3.94" × 1.34") Product Dimensions $(L \times W \times H)$

Net Weight 0.11 kg (0.24 lb)

What's in the box



Tools:

Documents: QR Code×1

Power:

Installation Position Map×1

Screw Package×1

Quick Start Guide×1

Legal and Regulation Bracket×1 Information×1

Power Adapter×1



