

CERTIFICATE OF CONSTANCY OF PERFORMANCE

0905-CPR-201263

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product(s)

Product(s): **Wireless Sounders and Visual alarm devices**
(refer to attached appendix for details and conditions)
Placed on the market
under the name or trade mark of: **Notifier by Honeywell, Pittway Tecnologica Srl**
Via Caboto 19/3
IT-34147 TRIESTE
Italy

and produced in the
manufacturing plant(s): **Pittway Tecnologica Srl (SG- 15617)**
Via Caboto 19/3
34147 Trieste
Italy

Intended use: **Fire Safety**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s):

EN 54-25:2008+AC:2012
EN 54-3:2001+A1:2002+A2:2006
EN 54-23:2010

Under System 1 for the performance set out in this certificate are applied and that the performance of the construction product is assessed to remain constant.

This certificate was first issued on 2020-07-21 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Notified Body
0905

Certification Manager: Dipl.-Ing. Roland Heine

Date Issue: 2020-07-21

Issue: 1

Signature:



This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Deutschland GmbH, Stangenstraße 1, 70771 Leinfelden-Echterdingen
Tel.: +49 711 27311-0 E-Mail: nb0905@intertek.com Web: www.intertek.de

CERTIFICATE OF CONSTANCY OF PERFORMANCE

0905-CPR-201263

APPENDIX TO: Certificate of Constancy of Performance 0905-CPR-201263

The details and conditions of use for the Wireless Sounders and Visual alarm devices , placed on the market under the name or trade mark of:

Notifier by Honeywell, Pittway Tecnologica Srl

Via Caboto 19/3

IT-34147 TRIESTE

Italy

To be used in accordance with the supplier's installation instructions and in conjunction with the following bases, ancillaries, sounder tones and sensitivity settings (*where applicable*):

Products compliant with EN 54-25:2008+AC:2012, EN 54-3:2001+A1:2002+A2:2006 and EN 54-23:2010.

Model	Manufacturing Location	Description
NRX-WSF-RR	SG-15617	Wall mount Sounder VAD – Red LED, Red Lens
NRX-WSF-RW	SG-15617	Wall mount Sounder VAD – Red LED, Clear Lens

Bases: The products were approved for use with the following mounting bases

Model B501RF Mounting base (white)

Model B501RF-RR Mounting base (red)

Approved Batteries:

Duracell Ultra 123 (lithium)

Panasonic Industrial 123 (lithium)

CERTIFICATE OF CONSTANCY OF PERFORMANCE

0905-CPR-201263

APPENDIX TO: Certificate of Constancy of Performance 0905-CPR-201263

Compliant settings: The products listed had the following approved settings:

Models NRX-WSF-RR, NRX-WSF-RW, have the following compliant settings in accordance with EN54-3:2001+A1:2002+A2:2006, at the maximum volume setting:

Tone No.	Description
1	Fire French Sound AFNOR (554/440 Hz)
2	800 Hz / 970 Hz
3	Alternating Tone Telecoms (800 Hz / 970 Hz)
4	Alternating High Frequency (2400 Hz / 2900 Hz)
5	Security Alarm (2500 Hz / 3100 Hz)
6	988 Hz / 645 Hz
7	All Clear (660 Hz)
8	970 Hz
9	1200 Hz
10	HF Continuous (2850 Hz)
11	GasAlarm Tone (150-1000 Hz)
12	AS2220 Alert Tone (420 Hz)
13	AS2220 Evacuate Tone (500 Hz / 1200 Hz)
14	Swedish Alarm Tone (660 Hz)
15	Intermittent Tone (970 Hz)
16	Backup Alarm LF & BS5839 pt1 (660 Hz)
17	Backup Alarm HF & BS5839 pt1 – Second Tone (2850 Hz)
18	LF BS5839 pt1 (970 Hz)
19	Intermittent (950 Hz)
20	800 Hz
21	Sweep (400-1200 Hz)
22	Evacuate DIN Tone & PFEER (1200-500 Hz)
23	Fast Sweep VdS (2400-2850 Hz)
23	Slow Whoop Evacuate Netherlands (500-1200 Hz)
25	LF Buzz BS5839 pt1 (800-970 Hz)
26	Fast Sweep LF BS5839 pt1 (800-970 Hz)
27	Medium Sweep LF BS5839 pt1 VdS (800-970 Hz)
28	High Frequency Buzz (2400-2850 Hz)
29	Fast Whoop (500-1000 Hz)
30	Siren Style tone (500-1200-500 Hz)
31	Sweep (800-1000 Hz)
32	Sweep (2400-2850 Hz)
33	33 – 4000 Hz
34	440 Hz
35	554 Hz
36	Intermittent 13s off (660 Hz)
37	Intermittent 1.8s off (660 Hz)
38	Pelican Crossing (2850 Hz)

Conditions of use:

Suitable for indoor applications

General Notes:

1. Evaluated under Intertek project number 104168456.
2. No CE or other type approval is made or inferred outside of the attestation of conformity and the product performance as stipulated on this certificate.

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.